

## Redmine - Feature #11469

### JSONP support

2012-07-20 17:27 - Markus M

<b>Status:</b>	Closed	<b>Start date:</b>	
<b>Priority:</b>	Normal	<b>Due date:</b>	
<b>Assignee:</b>	Jean-Philippe Lang	<b>% Done:</b>	0%
<b>Category:</b>	REST API	<b>Estimated time:</b>	0.00 hour
<b>Target version:</b>	2.1.0		
<b>Resolution:</b>	Fixed		
<b>Description</b>			
Please enable <a href="#">JSONP</a>			
This is necessary when a JS-Client wants to call the Redmine API of another Subdomain, Server, Protocol, Port... (Same Origin Policy)			
It's not that hard to accomplish. You just need to set a request filter that wraps the response in a given JS function. See <a href="#">#10761</a> for an example of the expected output.			
<b>Related issues:</b>			
Related to Redmine - Defect #10761: Rest API JSON response can not be parsed ...		<b>Closed</b>	
Related to Redmine - Feature #13718: Accept dots in JSONP callback		<b>Closed</b>	
Related to Redmine - Feature #12992: Make JSONP support optional and disabled...		<b>Closed</b>	

#### Associated revisions

##### Revision 10088 - 2012-07-27 21:56 - Jean-Philippe Lang

Adds JSONP support to the API (#11469).

#### History

##### #1 - 2012-07-21 18:09 - Etienne Massip

- Category set to REST API

##### #2 - 2012-07-22 22:53 - Jean-Philippe Lang

- Assignee set to Jean-Philippe Lang

- Target version set to 2.1.0

##### #3 - 2012-07-27 21:58 - Jean-Philippe Lang

- Subject changed from Enable JSONP to JSONP support

- Status changed from New to Closed

- Resolution set to Fixed

Support for JSONP added in [r10088](#). You can use the callback or jsonp parameter to specify the JSONP callback.

Exemple:

```
GET /issues.json?callback=foo
=> foo({"issues":...})
```

##### #4 - 2014-12-12 14:09 - Hai-Nam Nguyen

If you come into this page by searching, since [#12992](#) JSONP support is disabled by default.

##### #5 - 2015-01-10 18:18 - Toshi MARUYAMA

- Related to Feature #12992: Make JSONP support optional and disabled by default added