

Redmine - Defect #13

Files in repository have Windows-style line endings

2007-03-12 12:20 - Jonathan Dance

Status: Closed	Start date:
Priority: Normal	Due date:
Assignee:	% Done: 0%
Category:	Estimated time: 0.00 hour
Target version:	Affected version:
Resolution:	
Description	
<p>All files in the repository have Windows-style line endings (\r\n) - they should have svn:eol-style set to "native" so that this is not an issue for those users who try to view the source on other operating systems.</p> <p>The easy way to apply this change is as such:</p> <pre>/redmine \$ find . grep rb\$ xargs svn propset svn:eol-style native /redmine \$ find . grep rhtml\$ xargs svn propset svn:eol-style native</pre>	

History

#1 - 2007-04-18 17:16 - Pavol Murin

I second this - please, it makes the default svn diff unusable,

I always have to use external diff when creating patches.

muro

#2 - 2007-03-13 22:42 - Chris Grant

True ... submitted a patch the other day and it was a bit longer than needed because of the line endings.

I've got the following sitting in my ~/.subversion/config file

... it covers a lot of bases:

[miscellany]

enable-auto-props = yes

[auto-props]

Changelog = svn:eol-style=native

ChangeLog = svn:eol-style=native

CHANGELOG = svn:eol-style=native

Copying = svn:eol-style=native

COPYING = svn:eol-style=native

Install = svn:eol-style=native

INSTALL = svn:eol-style=native

KEYS = svn:eol-style=native

Makefile = svn:eol-style=native

Rakefile = svn:eol-style=native

Readme = svn:eol-style=native

ReadMe = svn:eol-style=native

README = svn:eol-style=native
UPGRADING = svn:eol-style=native
Licence = svn:eol-style=native
LICENCE = svn:eol-style=native
License = svn:eol-style=native
LICENSE = svn:eol-style=native
-LICENSE = svn:eol-style=native
abs-linkmap = svn:eol-style=native
abs-menulinks = svn:eol-style=native
.aart = svn:eol-style=native
.ac = svn:eol-style=native
.am = svn:eol-style=native
.bat = svn:eol-style=native
.builder = svn:eol-style=native
.c = svn:eol-style=native
.cat = svn:eol-style=native
.cgi = svn:eol-style=native
.classpath = svn:eol-style=native
.cmd = svn:eol-style=native
.config = svn:eol-style=native
.cpp = svn:eol-style=native
.css = svn:eol-style=native
.cwiki = svn:eol-style=native
.data = svn:eol-style=native
.dcl = svn:eol-style=native
.doc = svn:mime-type=application/msword
.dsp = svn:eol-style=CRLF
.dsw = svn:eol-style=CRLF
.dtd = svn:eol-style=native
.egrm = svn:eol-style=native
.ent = svn:eol-style=native
.erb = svn:eol-style=native
.ft = svn:eol-style=native
.fn = svn:eol-style=native
.fv = svn:eol-style=native
.grm = svn:eol-style=native
.g = svn:eol-style=native
.h = svn:eol-style=native
.htaccess = svn:eol-style=native
.htm = svn:eol-style=native
.html = svn:eol-style=native
.ico = svn:mime-type=image/x-icon
.ihtml = svn:eol-style=native
.in = svn:eol-style=native
.java = svn:eol-style=native
.jmx = svn:eol-style=native
.jpg = svn:mime-type=image/jpeg
.jsp = svn:eol-style=native
.js = svn:eol-style=native
.junit = svn:eol-style=native
.jx = svn:eol-style=native
.ldif = svn:eol-style=native
.log = svn:eol-style=native

.manifest = svn:eol-style=native
.m4 = svn:eol-style=native
.mf = svn:eol-style=native
.MF = svn:eol-style=native
.meta = svn:eol-style=native
.mod = svn:eol-style=native
.n3 = svn:eol-style=native
.pdf = svn:mime-type=application/pdf
.pen = svn:eol-style=native
.pl = svn:eol-style=native
.pm = svn:eol-style=native
.png = svn:mime-type=image/png
.pod = svn:eol-style=native
.pom = svn:eol-style=native
.project = svn:eol-style=native
.properties = svn:eol-style=native
.py = svn:eol-style=native
.rake = svn:eol-style=native
.rb = svn:eol-style=native
.rdf = svn:eol-style=native
.rhtml = svn:eol-style=native
.rnc = svn:eol-style=native
.rng = svn:eol-style=native
.rnx = svn:eol-style=native
.roles = svn:eol-style=native
.rss = svn:eol-style=native
.sh = svn:eol-style=native
.sql = svn:eol-style=native
.svg = svn:eol-style=native
.tld = svn:eol-style=native
.txt = svn:eol-style=native
.types = svn:eol-style=native
.vm = svn:eol-style=native
.vsl = svn:eol-style=native
.wsdd = svn:eol-style=native
.wsdl = svn:eol-style=native
.xargs = svn:eol-style=native
.xcat = svn:eol-style=native
.xconf = svn:eol-style=native
.xegrm = svn:eol-style=native
.xgrm = svn:eol-style=native
.xhtml = svn:eol-style=native
.xhtml2 = svn:eol-style=native
.xlex = svn:eol-style=native
.xlog = svn:eol-style=native
.xmap = svn:eol-style=native
.xml = svn:eol-style=native
.xroles = svn:eol-style=native
.xsamples = svn:eol-style=native
.xsd = svn:eol-style=native
.xsl = svn:eol-style=native
.xslt = svn:eol-style=native
.xsp = svn:eol-style=native

.xul = svn:eol-style=native
.xweb = svn:eol-style=native
.xwelcome = svn:eol-style=native
.yaml = svn:eol-style=native
.yml = svn:eol-style=native

#3 - 2007-03-13 21:27 - Jonathan Dance

Yes, as long as it's not a binary file. :)

The main reason I mentioned rb and rhtml files is for submitting patches, which are most likely to these files.

#4 - 2007-03-13 18:55 - Chris Grant

This should really be set on most (if not all) of the files, not just .rb and .rhtml files.

#5 - 2008-02-05 19:54 - Thomas Lecavelier

Hum... This issue seems to be closed, since I hadn't seen a ^M char in my vim since a long time ago. Somebody still have EOL problems with redmine sources?

#6 - 2008-02-05 20:57 - Jean-Philippe Lang

- Status changed from New to Closed

You're right.

There may be some migrations with such eol, but that's not the kind of files that should be patched so often.