## Redmine - Feature #13038

# Base path for filesystem repository adapter

2013-01-30 21:39 - Anonymous

Status:	Closed	Start date:	
Priority:	Normal	Due date:	
Assignee:		% Done:	0%
Category:	SCM	Estimated time:	0.00 hour
Target version:			
Resolution:	Duplicate		

## Description

It would be very helpful to have a field in administrative settings for a custom root when using file system repositories. Preventing access to '/' for every project's manager would be quite a challenge, so limiting that risk to admin users goes a long way.

I don't have the skills to offer an example patch, but it seems as simple as:

- 1. Adding a value to the settings table
- 2. Adding a form field to the administrative repository settings page that writes to that value
- 3. Updating /lib/redmine/scm/adapters/filesystem\_adapter.rb to include that value when it defines @url

Correct me if I'm wrong about the scope of work.

And thanks!

### Related issues:

Related to Redmine - Feature #1415: Let system administrator limit repositori... Closed 2008-06-09

### History

## #1 - 2013-02-02 09:24 - Toshi MARUYAMA

- Category changed from Administration to SCM

# #2 - 2013-03-07 00:15 - Anonymous

I believe I was able to do this pretty well on my own, and I think it's safe and general-purpose enough that it should be made part of basic Redmine functionality. Here's what I did:

- 1. Add to settings table a value filesystem\_base\_path.
- 2. /config/settings.yml needs to describe this value, so somewhere along the way make sure it includes:

```
filesystem_base_path:
default: ''
```

3. /locales/ needs a string to use as a label. In my case, I updated en.yml by finding where the 'setting\_' entries all were and adding:

```
setting_filesystem_base_path: Filesystem base path
```

4. /app/views/settings/\_repositories.html.erb is the Administrative settings panel for repositories, and a good place to add a field for users to set this value. Wherever you'd like, add the field (I just duplicated the repository\_log\_display\_limit field):

```
<%= setting_text_field :filesystem_base_path, :size => 6 %>
```

5. /lib/redmine/scm/adapters/filesystem\_adapter.rb is where the magic happens. Toward the very beginning, you'll find a line that reads:

```
@url = with_trailling_slash(url)
```

There may be better places or better code for this step, but I modified this line to read:

```
@url = with_trailling_slash(Setting.filesystem_base_path) + with_trailling_slash(url)
```

2025-07-05

This concatenates the base path value and the individual repository's location, and makes sure there's a slash at the end of your base path before doing so.

And unless I missed one of my steps, that should do it. You now have a setting restricted to administrators to set a global base path for file system repositories.

This is an under-used and under-appreciated module, but can be ridiculously powerful. A great example would be anyone using a newer version of the DMSF plugin with WebDAV enabled: have your Redmine server mount itself at the WebDAV root (<a href="http://redmine/dmsf/webdav">http://redmine/dmsf/webdav</a>) using admin credentials and set that mount point as your base path. Now from any project, add a file system repository and simply use the project identifier as the repository path, gaining access to many separate DMSFs from one project point and give the finger to duplication.

## #3 - 2014-11-07 02:44 - Go MAEDA

- Related to Defect #18291: Path property security issue when adding filesystem repository added

### #4 - 2014-11-08 11:58 - Jean-Philippe Lang

- Status changed from New to Closed
- Resolution set to Duplicate

Closing as a dup of #1415 which is addressed for 3.0 by adding configuration settings to limit valid repository path.

### #5 - 2014-11-08 11:58 - Jean-Philippe Lang

- Related to Feature #1415: Let system administrator limit repositories valid sources added

### #6 - 2014-11-08 11:59 - Jean-Philippe Lang

- Related to deleted (Defect #18291: Path property security issue when adding filesystem repository)

2025-07-05 2/2