

Redmine - Feature #13718

Accept dots in JSONP callback

2013-04-09 10:45 - Vitaliy Pitvalo

Status:	Closed	Start date:	
Priority:	Normal	Due date:	
Assignee:	Jean-Philippe Lang	% Done:	0%
Category:	REST API	Estimated time:	0.00 hour
Target version:	3.3.0		
Resolution:	Fixed		
Description			
When i try use mootools Request.JSONP Request it's not working. For example http://avtehnik.m.redmine.org/projects.json?callback=my.Handler&key=0e96523a813ecf559ddba696a4f9549489aa8781 , the callback is my.Handler but in response dot is not appear myHandler({"projects":....			
Related issues:			
Related to Redmine - Feature #11469: JSONP support			Closed

Associated revisions

Revision 15066 - 2016-01-16 10:08 - Jean-Philippe Lang

Accept dots in JSONP callback (#13718).

History

#1 - 2013-04-09 14:47 - Etienne Massip

- Tracker changed from Defect to Feature
- Subject changed from Dots in JSONP Callback handler to Extend JSONP callback handler syntax support
- Target version set to Candidate for next major release

According to json-p.org The proposed solution, allowed syntax could include these forms:

```
functionName ({JSON});  
obj.functionName ({JSON});  
obj["function-name"] ({JSON});
```

For now, only the first one is partly supported whith functionName bein composed of digits and characters A to Z plus _ (see [source:trunk/lib/redmine/views/builders/json.rb@11272#L30](https://trunk.lib.redmine.org/builders/json.rb@11272#L30)).

Theoretically functionName should also be checked as being a [valid javascript identifier name](#), thus allowing some Unicode characters, but this might look a bit overkill?

#2 - 2014-03-26 16:45 - Ken Franqueiro

I would definitely agree that at least foo.bar(...) support should be added (which I assume is what this issue originally asked for specifically, based on the subject history).

Some JS libraries e.g. Dojo use a global namespace for their JSONP request support so that only one global variable is created instead of multiple, and currently the regex in <http://www.redmine.org/projects/redmine/repository/entry/trunk/lib/redmine/views/builders/json.rb> will strip periods, making Redmine's JSONP REST API unusable with these JS libraries.

Here's an example of the kind of function names Dojo's dojo/request/script module uses: dojo_request_script_callbacks.dojo_request_script0

#3 - 2014-08-18 13:46 - Sam Blowes

Angular JS also uses object based JSONP callbacks.

Please support this ! :)

<https://github.com/angular/angular.js/issues/1551>

#4 - 2014-08-18 14:43 - Sam Blowes

I added the dot to the regex, which at least fixes the `obj.functionName({JSON})`; example.

<https://github.com/blowsie/redmine/commit/6d476160cdbc4eee17ae481f873fc07dc8cdf571>

#5 - 2015-05-29 23:37 - Brian Bouterse

I just spent several hours implementing workarounds because Redmine does not adhere to the JSONP specification. I'm still not done... I'm using Angular JS like the user in comment [#3](#). This issue is years old and has a link to a commit (comment [#4](#)) that contains a 1 line fix.

What needs to happen for this to be included in the next Redmine release.

#6 - 2015-06-28 13:16 - Toshi MARUYAMA

Sam Blowes wrote:

I added the dot to the regex, which at least fixes the `obj.functionName({JSON})`; example.

<https://github.com/blowsie/redmine/commit/6d476160cdbc4eee17ae481f873fc07dc8cdf571>

lib/redmine/views/builders/json.rb for trunk [r13339](#):

```
@@ -27,7 +27,7 @@ def initialize(request, response)
    super
    callback = request.params[:callback] || request.params[:jsonp]
    if callback && Setting.jsonp_enabled?
-     self.jsonp = callback.to_s.gsub(/[^a-zA-Z0-9_]/, '')
+     self.jsonp = callback.to_s.gsub(/[^a-zA-Z0-9_.]/, '')
    end
  end
end
```

#7 - 2015-12-17 11:58 - Sam Blowes

Could we pretty please have this single character added to this line?

Just for your sanity here is a description of the regex;

```
// [^a-zA-Z0-9_.]
//
// Options: Case sensitive; ^$ match at line breaks; dot doesn't match line breaks; Regex syntax only
//
// Match any single character that is NOT present in the list below and that is NOT a line break character (line feed) «[^a-zA-Z0-9_.]»
//   A character in the range between "a" and "z" (case sensitive) «a-z»
//   A character in the range between "A" and "Z" (case sensitive) «A-Z»
//   A character in the range between "0" and "9" «0-9»
//   A single character from the list "_" «_.» «_.»
```

#8 - 2015-12-17 14:29 - Sam Blowes

Perhaps someone with SVN skills would kindly submit my patch to the Redmine SVN repo.

<https://github.com/redmine/redmine/pull/68>

Regards.

#9 - 2015-12-18 13:12 - Sam Blowes

<https://bitbucket.org/redmine/redmine/pull-requests/3/improve-jsonp-support/diff>

#10 - 2015-12-21 05:44 - Toshi MARUYAMA

- File *issue-13718.diff* added

- Target version changed from *Candidate* for next major release to *3.3.0*

Sam Blowes wrote:

<https://bitbucket.org/redmine/redmine/pull-requests/3/improve-jsonp-support/diff>

One of reasons which pull request is bad is if source repository is deleted, diff is also deleted.

#11 - 2016-01-16 10:08 - Jean-Philippe Lang

- *Subject changed from Extend JSONP callback handler syntax support to Accept dots in JSONP callback*
- *Status changed from New to Closed*
- *Assignee set to Jean-Philippe Lang*
- *Resolution set to Fixed*

Fix committed, thanks.

Files

issue-13718.diff	1.62 KB	2015-12-21	Toshi MARUYAMA
------------------	---------	------------	----------------