

Redmine - Defect #16619

Mailer.token_for generates invalid message_id when using from address with full name

2014-04-10 13:34 - David Robinson

Status:	Closed	Start date:	
Priority:	Normal	Due date:	
Assignee:	Jean-Philippe Lang	% Done:	0%
Category:	Email notifications	Estimated time:	0.00 hour
Target version:	2.5.2	Affected version:	2.4.4
Resolution:	Fixed		
Description			
The token generator in Mailer.rb (Mailer.token_for) has the following code:			
<pre>host = Setting.mail_from.to_s.gsub(%r{^.*@}, '')</pre>			
If you have configured Redmine to send from an address with both name and email, (f.ex. "Redmine Mailer< no-reply@redmine.org >") this results in a Message-id like the following being created:			
<pre><redmine.journal-2421.20140408113649@redmine.org>></pre>			
the double ">" at the end is considered illegal by some mail servers, and results in them rejecting it.			
A possible solution could be the following:			
<pre>host = Setting.mail_from.to_s.gsub(%r{(^.*@) >}, '')</pre>			

Associated revisions

Revision 13126 - 2014-05-02 09:56 - Jean-Philippe Lang

Mailer.token_for generates invalid message_id when using from address with full name (#16619).

Revision 13155 - 2014-05-24 18:29 - Jean-Philippe Lang

Merged r13126 (#16619).

History

#1 - 2014-05-02 09:56 - Jean-Philippe Lang

- Subject changed from Mailer.rb token generator to Mailer.token_for generates invalid message_id when using from address with full name
- Status changed from New to Resolved
- Assignee set to Jean-Philippe Lang
- Target version set to 2.5.2
- Resolution set to Fixed

Fixed in [r13126](#), thanks for pointing this out.

#2 - 2014-05-24 18:29 - Jean-Philippe Lang

- Status changed from Resolved to Closed

Merged.