Redmine - Defect #19276

Creating new issues with invalid project_id should return 422 instead of 403 error

2015-03-05 03:09 - hironemu @

Status:	Closed	Start date:	
Priority:	Normal	Due date:	
Assignee:	Jean-Philippe Lang	% Done:	0%
Category:	REST API	Estimated time:	0.00 hour
Target version:	3.0.2		
Resolution:	Fixed	Affected version:	3.0.0
Description		I	
Hi,			
The following REST	request worked fine in Redmine 2.6.0:		
ć]		00m -l	
	ontent-Type: application/xml" -X Po	OSTdata "@test	t.xml" -u test:testpass https://
\$ curl -v -H "C example.com/iss		OSTdata "@test	t.xml" -u test:testpass https://
example.com/iss		OSTdata "@test	t.xml" -u test:testpass https://
		OSTdata "@test	t.xml" -u test:testpass https://
example.com/iss		OST ——data "@test	t.xml" -u test:testpass https://
example.com/iss test.xml		OSTdata "@test	t.xml" -u test:testpass https://
example.com/iss test.xml	ues.xml	OST ——data "@test	t.xml" -u test:testpass https://
example.com/iss test.xml xml version="</td <td>ues.xml 1.0" encoding="ISO-8859-1" ?></td> <td>OST ——data "@test</td> <td>t.xml" -u test:testpass https://</td>	ues.xml 1.0" encoding="ISO-8859-1" ?>	OST ——data "@test	t.xml" -u test:testpass https://
example.com/iss test.xml xml version="<br <issue> <subject>test</subject></issue>	ues.xml 1.0" encoding="ISO-8859-1" ?>	OSTdata "@test	t.xml" -u test:testpass https://
example.com/iss test.xml xml version="<br <issue> <subject>test <project_id>t</project_id></subject></issue>	ues.xml 1.0" encoding="ISO-8859-1" ?> 	OST ——data "@test	t.xml" -u test:testpass https://
<pre>example.com/iss test.xml <?xml version=" <issue> <subject>test <project_id>t <tracker_id>6 <description></description></tracker_id></project_id></subject></pre>	ues.xml 1.0" encoding="ISO-8859-1" ?> est_project	OSTdata "@test	t.xml" -u test:testpass https://
<pre>example.com/iss test.xml <?xml version=" <issue> <subject>test <project_id>t <tracker_id>6</tracker_id></project_id></subject></pre>	ues.xml 1.0" encoding="ISO-8859-1" ?> est_project 	OST ——data "@test	t.xml" -u test:testpass https://
<pre>example.com/iss test.xml <?xml version=" <issue> <subject>test <project_id>t <tracker_id>6 <description> </description></tracker_id></project_id></subject></pre>	ues.xml 1.0" encoding="ISO-8859-1" ?> est_project test		t.xml" -u test:testpass https://
<pre>example.com/iss test.xml <?xml version=" <issue> <subject>test <project_id>t <tracker_id>6 <description> Since upgrading to F</description></tracker_id></project_id></subject></pre>	ues.xml 1.0" encoding="ISO-8859-1" ?> est_project 		t.xml" -u test:testpass https://
<pre>example.com/iss test.xml <?xml version=" <issue> <subject>test <project_id>t <tracker_id>6 <description> Since upgrading to F</description></tracker_id></project_id></subject></pre>	<pre>ues.xml 1.0" encoding="ISO-8859-1" ?> est_project test Redmine 3.0.0 the server responds with a HTTH</pre>		t.xml" -u test:testpass https://
example.com/iss test.xml xml version="<br <issue> <subject>test <project_id>t <tracker_id>6 <description> </description></tracker_id></project_id></subject></issue> Since upgrading to F I don't change user's Related issues:	<pre>ues.xml 1.0" encoding="ISO-8859-1" ?> est_project test Redmine 3.0.0 the server responds with a HTTH</pre>		t.xml" -u test:testpass https:// Closed 2008-04-05
example.com/iss test.xml xml version="<br <issue> <subject>test <project_id>t <tracker_id>6 <description> </description></tracker_id></project_id></subject></issue> Since upgrading to F I don't change user's Related issues: Related to Redmine - F	<pre>ues.xml 1.0" encoding="ISO-8859-1" ?> est_project test Redmine 3.0.0 the server responds with a HTTP strole or other permissions.</pre>	P 403 Forbidden.	

Associated revisions

Revision 14141 - 2015-03-20 11:02 - Jean-Philippe Lang

API: creating an issue with an invalid project_id should return 422 instead of 403 (#19276).

Revision 14146 - 2015-03-20 17:27 - Jean-Philippe Lang

Don't render the issue form if issue.project is nil (#19276).

Revision 14150 - 2015-03-21 09:35 - Jean-Philippe Lang

Merged r14141 and r14146 (#19276).

History

#1 - 2015-03-07 08:18 - Jean-Philippe Lang

- Status changed from New to Closed

- Resolution set to Wont fix

As you can see on the <u>API documentation</u>, the project_id attribute must be the numeric id of the project.

#2 - 2015-03-10 12:15 - Aron Rotteveel

That is actually not true. This has always worked. I am also getting 403's after upgrading. As your linked API documentation states:

#4 - 2015-03-11 15:39 - Toshi MARUYAMA

- Status changed from Closed to New
- Resolution deleted (Wont fix)

#5 - 2015-03-12 21:21 - Alex Last

same here. I installed Redmine 3.0.0 to our test server and tried running Redmine Java API tests against it:

com.taskadapter.redmineapi.NotAuthorizedException: Forbidden. Please check the user has proper permissions.

this worked fine with all previous Redmine versions.

#6 - 2015-03-12 21:28 - Alex Last

was "project key" requirement changed to "project numeric ID" somewhere between 2.6.2 and 3.0.0 releases? if yes, can we document this on REST Issue page in Wiki?

#7 - 2015-03-12 21:29 - Alex Last

and one other thing: if project ID cannot be parsed then there should be a proper error returned to clients, not "forbidden" - that one is totally misleading.

#8 - 2015-03-16 23:48 - Jean-Philippe Lang

- Subject changed from Creating new issues through REST API 403 in Redmine 3.0.0 to Creating new issues with invalid project_id results in 403 error

- Target version set to Candidate for next minor release

Aron Rotteveel wrote:

That is actually not true. This has always worked. I am also getting 403's after upgrading. As your linked API documentation states:

Project identifier can be used as a filter and even if it used to work, it was never supposed to be used as a project_id value when creating an issue, as you can see in the api tests: <u>source:/trunk/test/integration/api_test/issues_test.rb</u> or in the <u>curl example</u>. It's consistent with other API endpoints that take a project id (project.parent_id and time_entry.project_id) and consistent with API responses. The API doc should be updated.

and one other thing: if project ID cannot be parsed then there should be a proper error returned to clients, not "forbidden" - that one is totally misleading.

A 422 response would be a better option indeed.

#9 - 2015-03-20 11:03 - Jean-Philippe Lang

- Subject changed from Creating new issues with invalid project_id results in 403 error to Creating new issues with invalid project_id should return 422 instead of 403 error

- Status changed from New to Resolved

- Assignee set to Jean-Philippe Lang
- Target version changed from Candidate for next minor release to 3.0.2

- Resolution set to Fixed

#10 - 2015-03-21 09:35 - Jean-Philippe Lang

- Status changed from Resolved to Closed

#11 - 2015-06-18 08:32 - Alexander Muthmann

Note: the documentation still states

project_id: get issues from the project with the given id, where id is either project id or project identifier

which is quite confusing.

#12 - 2015-06-29 04:05 - Go MAEDA

- Has duplicate Defect #20119: REST API: setting project_id in issue not accepted in Redmine 3.0.3 added

#13 - 2015-06-29 04:40 - Go MAEDA

Alexander Muthmann wrote:

Note: the documentation still states [...] which is quite confusing.

Thanks for pointing it out. I have fixed the document.

project_id: get issues from the project with the given id (a numeric value, not a project identifier).

#14 - 2015-07-29 04:02 - Mischa The Evil

- Related to Feature #1003: Allow "New Issue" from anywhere added

#15 - 2016-11-23 10:31 - Go MAEDA

- Related to Defect #23766: API : creating issues with project identifier no longer possible added