

Redmine - Defect #2286

Pb with CVS Server when CVSROOT does not contain user name

2008-12-06 12:39 - Jerome Vanthournout

Status:	Closed	Start date:	2008-12-06
Priority:	Normal	Due date:	
Assignee:		% Done:	0%
Category:	SCM	Estimated time:	0.00 hour
Target version:	0.8	Affected version:	0.7.3
Resolution:	Fixed		

Description

Depending on the CVS configuration, it is not mandatory to include a username in the CVSROOT.
For example, a valid CVSROOT is :ext:cvsservername:/cvsdatabase/projects1
With this CVSROOT format, redmine does not import correctly the information from CVS but does not report any error.
When configuring the CVSROOT with a username, :ext:username@cvsservername:/cvsdatabase/projects1, everything goes well.

The problem comes from the file name lib/redmine/scm/adapters/cvs_adapter.rb.
In the regular expression line 137 `root_url.gsub(/^:.*[^\s:]+:\d*/, "")`, the `^:` should be optional.

History

#1 - 2008-12-06 13:07 - Jerome Vanthournout

I forget one char in the previous description.

The problem comes from the file name lib/redmine/scm/adapters/cvs_adapter.rb.
In the regular expression line 137 `root_url.gsub(/^:.*[^\s:]+:\d*/, "")`, the `@` should be optional.

#2 - 2008-12-06 18:41 - Jean-Philippe Lang

- Status changed from New to Closed
- Target version set to 0.8
- Resolution set to Fixed

Fixed in [r2096](#). Thanks for pointing this out.