

Redmine - Defect #3462

CVS: Repository path encoding of non UTF-8 characters

2009-06-08 16:24 - Rodrigo Rosenfeld Rosas

Status:	Closed	Start date:	2009-06-08
Priority:	Low	Due date:	
Assignee:	Toshi MARUYAMA	% Done:	0%
Category:	SCM	Estimated time:	0.00 hour
Target version:	1.2.0	Affected version:	
Resolution:	Fixed		
Description			
<p>We have some "ISO-8859-1" encoded filenames in our CVS repository. Repository.find(20).fetch_updates yields this error:</p> <pre>ActiveRecord::StatementInvalid (PGError: ERROR: invalid byte sequence for encoding "UTF8": 0xf3706961 HINT: This error can also happen if the byte sequence does not match the encoding expected by the server, which is controlled by "client_encoding". : SELECT "changes".* FROM "changes" INNER JOIN changesets ON changes.changeset_id = changesets.id WHERE ("changes"."revision" = E'1.2.' AND "changes"."path" = E'/xxxxx/AlterarSenha (c<F3>pia).png') AND (("changesets".repository_id = 20)) LIMIT 1): ... The attached patch solved the problem for us.<p>Above is the relevant stack:</p><pre>/opt/redmine/.gem/ruby/1.8/gems/activerecord-2.2.2/lib/active_record/connection_adapters/abstract_adapter.rb:188:in `log' /opt/redmine/.gem/ruby/1.8/gems/activerecord-2.2.2/lib/active_record/connection_adapters/postgresql_adapter.rb:503:in `execute' /opt/redmine/.gem/ruby/1.8/gems/activerecord-2.2.2/lib/active_record/connection_adapters/postgresql_adapter.rb:1000:in `select_raw' /opt/redmine/.gem/ruby/1.8/gems/activerecord-2.2.2/lib/active_record/connection_adapters/postgresql_adapter.rb:987:in `select' /opt/redmine/.gem/ruby/1.8/gems/activerecord-2.2.2/lib/active_record/connection_adapters/abstract/database_statements.rb:7:in `select_all_without_query_cache' /opt/redmine/.gem/ruby/1.8/gems/activerecord-2.2.2/lib/active_record/connection_adapters/abstract/query_cache.rb:60:in `select_all' /opt/redmine/.gem/ruby/1.8/gems/activerecord-2.2.2/lib/active_record/connection_adapters/abstract/query_cache.rb:81:in `cache_sql' /opt/redmine/.gem/ruby/1.8/gems/activerecord-2.2.2/lib/active_record/connection_adapters/abstract/query_cache.rb:60:in `select_all' /opt/redmine/.gem/ruby/1.8/gems/activerecord-2.2.2/lib/active_record/base.rb:635:in `find_by_sql' /opt/redmine/.gem/ruby/1.8/gems/activerecord-2.2.2/lib/active_record/base.rb:1490:in `find_every' /opt/redmine/.gem/ruby/1.8/gems/activerecord-2.2.2/lib/active_record/base.rb:1452:in `find_initial' /opt/redmine/.gem/ruby/1.8/gems/activerecord-2.2.2/lib/active_record/base.rb:587:in `find' /opt/redmine/.gem/ruby/1.8/gems/activerecord-2.2.2/lib/active_record/base.rb:1812:in `find_by_path_and_revision' /opt/redmine/.gem/ruby/1.8/gems/activerecord-2.2.2/lib/active_record/associations/association_collection.rb:370:in `send' /opt/redmine/.gem/ruby/1.8/gems/activerecord-2.2.2/lib/active_record/associations/association_collection.rb:370:in `method_missing' /opt/redmine/.gem/ruby/1.8/gems/activerecord-2.2.2/lib/active_record/base.rb:2003:in `with_scope' /opt/redmine/.gem/ruby/1.8/gems/activerecord-2.2.2/lib/active_record/associations/association_proxy.rb:202:in `send' /opt/redmine/.gem/ruby/1.8/gems/activerecord-2.2.2/lib/active_record/associations/association_proxy.rb:202:in `with_scope' /opt/redmine/.gem/ruby/1.8/gems/activerecord-2.2.2/lib/active_record/associations/association_collection.rb:366:in `method_missing' /app/models/repository/cvs.rb:107:in `fetch_changesets' /lib/redmine/scm/adapters/cvs_adapter.rb:192:in `revisions' /lib/redmine/scm/adapters/cvs_adapter.rb:126:in `each_line' /lib/redmine/scm/adapters/cvs_adapter.rb:126:in `revisions' /lib/redmine/scm/adapters/abstract_adapter.rb:181:in `call' /lib/redmine/scm/adapters/abstract_adapter.rb:181:in `shellout' /lib/redmine/scm/adapters/abstract_adapter.rb:179:in `popen' /lib/redmine/scm/adapters/abstract_adapter.rb:179:in `shellout' /lib/redmine/scm/adapters/abstract_adapter.rb:165:in `shellout' /lib/redmine/scm/adapters/cvs_adapter.rb:114:in `revisions' /app/models/repository/cvs.rb:104:in `fetch_changesets' /opt/redmine/.gem/ruby/1.8/gems/activerecord-2.2.2/lib/active_record/connection_adapters/postgresql_adapter.rb:550:in `transaction' /opt/redmine/.gem/ruby/1.8/gems/activerecord-2.2.2/lib/active_record/transactions.rb:129:in `transaction' /opt/redmine/.gem/ruby/1.8/gems/activerecord-2.2.2/lib/active_record/transactions.rb:138:in `transaction' /app/models/repository/cvs.rb:102:in `fetch_changesets'</pre></pre>			
Related issues:			

Associated revisions

Revision 5461 - 2011-04-15 09:15 - Toshi MARUYAMA

scm: cvs: set path encoding instance value (#3462).

Revision 5462 - 2011-04-15 09:16 - Toshi MARUYAMA

scm: cvs: convert encoding of command line arguments (#3462).

Revision 5463 - 2011-04-15 09:16 - Toshi MARUYAMA

scm: cvs: convert encoding paths in revisions() of adapter (#3462).

Revision 5464 - 2011-04-15 09:17 - Toshi MARUYAMA

scm: cvs: convert encoding paths in entries() of adapter (#3462).

Revision 5465 - 2011-04-15 09:18 - Toshi MARUYAMA

scm: cvs: add path encoding select box at setting (#3462).

Revision 5520 - 2011-04-23 05:35 - Toshi MARUYAMA

scm: use i18n string at path encoding setting (#2274, #2664, #3462, #5251).

Revision 5521 - 2011-04-23 05:35 - Toshi MARUYAMA

scm: add Japanese translation "field_scm_path_encoding" (#2274, #2664, #3462, #5251).

Revision 5522 - 2011-04-23 05:36 - Toshi MARUYAMA

scm: update locales for path encoding setting (#2274, #2664, #3462, #5251).

Revision 5523 - 2011-04-23 05:36 - Toshi MARUYAMA

scm: use i18n string at path encoding setting note (#2274, #2664, #3462, #5251).

Revision 5524 - 2011-04-23 05:37 - Toshi MARUYAMA

scm: add Japanese string at path encoding setting note (#2274, #2664, #3462, #5251).

Revision 5525 - 2011-04-23 05:37 - Toshi MARUYAMA

scm: update locales for path encoding setting note (#2274, #2664, #3462, #5251).

Revision 5630 - 2011-05-04 07:02 - Toshi MARUYAMA

scm: cvs: fix loss non ASCII paths if path_encoding is " (#3462).

Revision 5863 - 2011-05-21 04:16 - Toshi MARUYAMA

scm: add "path_encoding" method in abstract adapter (#2274, #3462, #2664, #5251).

Revision 5866 - 2011-05-21 04:18 - Toshi MARUYAMA

scm: cvs: override "path_encoding" method in adapter (#3462).

Revision 5867 - 2011-05-21 04:19 - Toshi MARUYAMA

scm: cvs: add unit adapter test of default path_encoding is UTF-8 (#3462).

History

#1 - 2011-02-08 05:53 - Toshi MARUYAMA

- Assignee set to Toshi MARUYAMA
- Priority changed from High to Normal

#2 - 2011-02-21 01:46 - Toshi MARUYAMA

- Assignee deleted (Toshi MARUYAMA)
- Priority changed from Normal to Low

Ruby 1.9 compatibility is very serious.

#3 - 2011-04-15 09:00 - Toshi MARUYAMA

- Assignee set to Toshi MARUYAMA

#4 - 2011-04-15 09:01 - Toshi MARUYAMA

- Subject changed from CVS path encoding problems to CVS: Repository path encoding of non UTF-8 characters

#5 - 2011-04-15 09:21 - Toshi MARUYAMA

- Target version set to 1.2.0

#6 - 2011-04-15 09:24 - Toshi MARUYAMA

- Status changed from New to Closed

- Resolution set to Fixed

I finished implementing in [r5465](#).

I can not prepare test repository for same reason with filesystem repository [#2274](#).

If tar ball has Latin-1 path encoding files, I can't extract it on my Japanese Windows.

There are same limitations with git [#5251](#).

Files

cvs-path-encoding.patch	471 Bytes	2009-06-08	Rodrigo Rosenfeld Rosas
-------------------------	-----------	------------	-------------------------