

## Redmine - Defect #35

### Incorrect links for the Admisitration menu

2007-04-05 07:57 - Mahmoud M'HIRI

<b>Status:</b>	Closed	<b>Start date:</b>	
<b>Priority:</b>	Normal	<b>Due date:</b>	
<b>Assignee:</b>		<b>% Done:</b>	0%
<b>Category:</b>		<b>Estimated time:</b>	0.00 hour
<b>Target version:</b>		<b>Affected version:</b>	
<b>Resolution:</b>			
<b>Description</b>			
<p>When deploying redmine in my server, all is ok but the administration sub-menus where not working in fact, i'm not deploying redmine in the root of my server:</p> <p><a href="http://www.myserevr.com/dir/subdir/redmine">www.myserevr.com/dir/subdir/redmine</a></p> <p>and all menues are pointing to</p> <p><a href="http://www.myserevr.com/dir/subdir/redmine/public/:controller/..">www.myserevr.com/dir/subdir/redmine/public/:controller/..</a></p> <p>but sub menues of Administration are pointing to:</p> <p><a href="http://www.myserevr.com/:controller/..">www.myserevr.com/:controller/..</a></p> <p>so they are incorrect links, i just modified the app/views/layout/base.rhtml to add my root the DIVs of those sub menues.</p> <p>I think that this should be managed by a variable in enviremont.rb or sth like that..</p>			

#### History

##### #1 - 2007-04-05 10:49 - Jean-Philippe Lang

In fact, this bug was fixed several weeks ago in the repository.  
You can check out the latest source or wait for the next release to have this fix.

To check out the source (you need the svn binaries):  
svn checkout svn://rubyforge.org/var/svn/redmine/trunk

##### #2 - 2007-04-08 03:59 - Mahmoud M'HIRI

I think that the same "bug" is till unfixed enven in the repository. In fact when clicking the "Help" button it is redirecting to "/manual/#{lang}/#{template}" which do not include the host path (the problem is raisen only when redmine is hosted in subdirectories), so if we trust on the host name given in the settings, we could correct this by substituting reirection in help\_controller.rb by:

```
if template
  link = Setting.host_name
  redirect_to
"http://#{Setting.host_name}/manual/#{lang}/#{template}"
;
  else
    redirect_to
"http://#{Setting.host_name}/manual/#{lang}/index.html"
  end
end
```

##### #3 - 2007-04-08 14:18 - Jean-Philippe Lang

I've fixed the help link (not exactly the way you propose).

Thanks

**#4 - 2007-04-08 15:53 - Mahmoud M'HIRI**

But why not to use the same way (request.relative\_url\_root) for mail notification instead of asking host\_name ?

**#5 - 2007-04-08 16:27 - Jean-Philippe Lang**

Because request.relative\_url\_root doesn't give you a host name, just a path.

**#6 - 2007-04-09 06:10 - Mahmoud M'HIRI**

So what do you say about:

```
url = "http://" + request.domain + "/"
```

instead of:

```
url = "http://#{Setting.host_name}/"
```

**#7 - 2007-04-10 10:43 - Mahmoud M'HIRI**

It isn't from mailer.rb ( url = "http://#{Setting.host\_name}/") that we extract host name ?