

Redmine - Defect #6667

REST API call with POST/PUT

2010-10-14 11:06 - Afsar Red

Status:	New	Start date:	2010-10-14
Priority:	Normal	Due date:	
Assignee:	Jean-Philippe Lang	% Done:	0%
Category:	REST API	Estimated time:	0.00 hour
Target version:		Affected version:	
Resolution:			
Description			
Hi, I could not able to create a project OR issue using redmine API call. just wanted to know, whether I made any mistake on the following CURL command for creating a new project: =====			
<pre>curl -X POST -d '<?xml version="1.0" encoding="UTF-8"?> <projects type="array"> <project> <name>Redmine</name> <identifier>redmine</identifier> <description>Redmine is a flexible project management web application written using Ruby on Rails framework.</description> </project> </projects>' -H 'Content-type:application/xml' -u asami_morita http://hostname/projects.xml</pre>			
=====			
Thanks			

History

#1 - 2010-10-14 19:39 - Felix Schäfer

Have you activated the REST API? What error are you getting from that command (use -v to see what HTTP error exactly your redmine returns)? What error does that call yield in the redmine log (log/development.log or log/production.log)?

#2 - 2010-10-15 11:37 - Afsar Red

Thanks for the quick response, Felix.

It gives the following error message, when I place verbose option.

```
.
.
.
<!DOCTYPE HTML PUBLIC "-//IETF//DTD HTML 2.0//EN">
<html><head>
<title>401 Authorization Required</title>
</head><body>
<h1>Authorization Required</h1>
<p>This server could not verify that you
are authorized to access the document
requested. Either you supplied the wrong
credentials (e.g., bad password), or your
browser doesn't understand how to supply
the credentials required.</p>
<hr>
<address>Apache/2.2.14 (Ubuntu) Server at development.avonvoices.com Port 80</address>
</body></html>
```

In the meantime, I could be able to get the list of projects by the following command using the same username and password:

curl -u [asami morita](#) -G <http://host/projects.xml?key=.....> -V

Thanks

#3 - 2010-10-16 20:30 - Holger Just

The REST API does **not** use your username and password via basic auth. Instead, each account has an assigned key (which you can find in the sidebar at <http://yourredmine.com/my/account>). That key is used exclusively for authentication, as you have done in your second example. The username and password were ignored completely.

#4 - 2010-10-18 11:23 - Afsar Red

Holger,
Thanks for the followup.
From the documentation(http://www.redmine.org/wiki/redmine/Rest_Projects), I found that, it could be able create a project by the following command:

```
curl -X POST -d '<?xml version="1.0" encoding="UTF-8"?><project><name>Redmine</name><identifier>redmin</identifier><description>Redmine is a flexible project management web application written using Ruby on Rails framework.</description></project>' -H 'Content-type:application/xml' http://hostname/projects.xml?key=.....
```

But, still I could not be able to create a new project. Note that I removed -u option from the command. Could you please look into this .

#5 - 2010-12-02 16:16 - Tomasz Muszyński

- Assignee set to Jean-Philippe Lang

I've modified one line of code to get this working.

```
url = url_for(:controller => params[:controller], :action => params[:action], :id => params[:id], :project_id => params[:project_id], :key => params[:key])
```

was changed in this code fragment in app/controllers/application_controller.rb:

```
def require_login
  if !User.current.logged?
    # Extract only the basic url parameters on non-GET requests
    if request.get?
      url = url_for(params)
    else
      url = url_for(:controller => params[:controller], :action => params[:action], :id => params[:id], :project_id => params[:project_id])
    end
    respond_to do |format|
      format.html { redirect_to :controller => "account", :action => "login", :back_url => url }
      format.atom { redirect_to :controller => "account", :action => "login", :back_url => url }
      format.xml { head :unauthorized, 'WWW-Authenticate' => 'Basic realm="Redmine API" }
      format.js { head :unauthorized, 'WWW-Authenticate' => 'Basic realm="Redmine API" }
      format.json { head :unauthorized, 'WWW-Authenticate' => 'Basic realm="Redmine API" }
    end
    return false
  end
  true
end
```

Unfortunately, i'm not a ruby programmer, so i'm not sure that above change is enough, but it's working for me.

Above solution fixes closed bug [#6447](#) which is still not working properly. Jean, I've assigned it to you as you closed [#6447](#) :)

#6 - 2011-03-23 09:38 - Toshi MARUYAMA

- Category set to REST API

#7 - 2012-02-21 07:15 - RedminePro Yang

Holger Just wrote:

The REST API does **not** use your username and password via basic auth. Instead, each account has an assigned key (which you can find in the sidebar at <http://yourredmine.com/my/account>). That key is used exclusively for authentication, as you have done in your second example. The username and password were ignored completely.

Why the API Access Key is not showed in <http://demo.redmine.org/my/account> any more?