

Redmine - Feature #7346

Allow a default version to be set on the command line for incoming emails

2011-01-17 08:06 - Garry Fallon

Status:	Closed	Start date:	2011-01-17
Priority:	Normal	Due date:	
Assignee:	Jean-Philippe Lang	% Done:	0%
Category:	Email receiving	Estimated time:	0.00 hour
Target version:	3.2.0		
Resolution:	Fixed		

Description

Feature [#5622](#) added support to allow the `target_version` (`fixed_version` in the implementation) to be set in the contents on an incoming email; this is a useful addition.

It would be really useful to also allow a default version to be set on the command line (for new tickets) when calling `receive_pop3` or `receive_imap`. This would be really useful in cases where you want all new tickets to be added to a version such as "Unassigned Backlog", "For Review", etc...

This is a very minor change to `redmine/lib/tasks/email.rake` to add `fixed_version` to the list of attributes that can be set for both `:receive_pop3` and `:receive_imap`, and add a relevant description to the command line help. e.g. replace `%w(project status tracker category priority).each { |a| options[:issue][a.to_sym] = ENV[a] if ENV[a] }` with `%w(project status tracker category priority fixed_version).each { |a| options[:issue][a.to_sym] = ENV[a] if ENV[a] }`

Associated revisions

Revision 14789 - 2015-11-01 09:56 - Jean-Philippe Lang

Allow a default version to be set on the command line for incoming emails (#7346).

History

#1 - 2015-11-01 09:56 - Jean-Philippe Lang

- Status changed from New to Closed
- Assignee set to Jean-Philippe Lang
- Target version set to 3.2.0
- Resolution set to Fixed

Feature added in [r14789](#).