# Redmine - Defect #11191

# receive\_imap failed with localizaed characters in attachments or subject

2012-06-18 15:12 - Arnis Juraga

Status: Closed Start date: **Priority:** Normal Due date: Assignee: % Done: 0% Category: **Estimated time:** 0.00 hour Email receiving Target version: Resolution: Affected version: Cant reproduce

# **Description**

Today I have noticed IMAP read problems, when email attachment is text file with localized characters. I had the same problem with email having localized characters in SUBJECT line, but cannot reproduce it anymore:

rake redmine:email:receive\_imap RAILS\_ENV="production" host=imap.gmail.com ssl=SSL port=993

username=XXXX@XXXX.XXX password=XXXXXXXXXXX move\_on\_success=izlasitie move\_on\_failure=failed proje

But I can reproduce problem with attachemnt.

export GEM\_HOME=/var/lib/gems/1.8/gems/
export PATH=/var/lib/gems/1.8/bin:\$PATH

/opt/redmine/redmine-2.0.2/lib/tasks/email.rake:133

/var/lib/gems/1.8/gems/rake-0.9.2.2/lib/rake/task.rb:205:in `call'/var/lib/gems/1.8/gems/rake-0.9.2.2/lib/rake/task.rb:205:in `execu/var/lib/gems/1.8/gems/rake-0.9.2.2/lib/rake/task.rb:200:in `each'/var/lib/gems/1.8/gems/rake-0.9.2.2/lib/rake/task.rb:200:in `execu

cd /opt/redmine/redmine-2.0.2/

rake task script:

#!/bin/bash

```
ct=incoming unknown_user=create no_permission_check=1 --trace
Trace result:
root@int:~# /opt/redmine/scripts/redminemail.sh
** Invoke redmine:email:receive_imap (first_time)
** Invoke environment (first_time)
** Execute environment
** Execute redmine:email:receive_imap
rake aborted!
"šrutu apraksti -"...
/var/lib/gems/1.8/gems/mail-2.4.4/lib/mail/message.rb:2046:in `conv'
/var/lib/gems/1.8/gems/mail-2.4.4/lib/mail/message.rb:2046:in `decode_body_as_text'
/var/lib/gems/1.8/gems/mail-2.4.4/lib/mail/message.rb:1786:in `decoded'
/opt/redmine/redmine-2.0.2/app/models/mail_handler.rb:245:in `add_attachments'
/opt/redmine/redmine-2.0.2/app/models/mail_handler.rb:243:in `each'
/opt/redmine/redmine-2.0.2/app/models/mail_handler.rb:243:in `add_attachments'
/opt/redmine/redmine-2.0.2/app/models/mail_handler.rb:175:in `receive_issue'
/opt/redmine/redmine-2.0.2/app/models/mail_handler.rb:152:in `dispatch_to_default'
/opt/redmine/redmine-2.0.2/app/models/mail_handler.rb:137:in `dispatch'
/opt/redmine/redmine-2.0.2/app/models/mail_handler.rb:113:in `receive'
/var/lib/gems/1.8/gems/actionmailer-3.2.5/lib/action_mailer/base.rb:404:in `receive'
/var/lib/gems/1.8/gems/activesupport-3.2.5/lib/active_support/notifications.rb:123:in `instrument'
/var/lib/gems/1.8/gems/activesupport-3.2.5/lib/active_support/notifications/instrumenter.rb:20:in
`instrument'
/var/lib/gems/1.8/gems/activesupport-3.2.5/lib/active_support/notifications.rb:123:in `instrument'
/var/lib/gems/1.8/gems/actionmailer-3.2.5/lib/action_mailer/base.rb:401:in `receive'
/opt/redmine/redmine-2.0.2/app/models/mail_handler.rb:44:in `receive'
/opt/redmine/redmine-2.0.2/lib/redmine/imap.rb:35:in `check'
/opt/redmine/redmine-2.0.2/lib/redmine/imap.rb:32:in
/opt/redmine/redmine-2.0.2/lib/redmine/imap.rb:32:in `check'
```

2025-05-01 1/8

/var/lib/gems/1.8/gems/rake-0.9.2.2/lib/rake/task.rb:158:in `invoke\_with\_call\_chain'

```
/usr/lib/ruby/1.8/monitor.rb:242:in `synchronize'
/var/lib/gems/1.8/gems/rake-0.9.2.2/lib/rake/task.rb:151:in `invoke_with_call_chain'
/var/lib/gems/1.8/gems/rake-0.9.2.2/lib/rake/task.rb:144:in `invoke'
/var/lib/gems/1.8/gems/rake-0.9.2.2/lib/rake/application.rb:116:in `invoke_task'
/var/lib/gems/1.8/gems/rake-0.9.2.2/lib/rake/application.rb:94:in `top_level'
/var/lib/gems/1.8/gems/rake-0.9.2.2/lib/rake/application.rb:94:in `each'
/var/lib/gems/1.8/gems/rake-0.9.2.2/lib/rake/application.rb:94:in `top_level'
/var/lib/gems/1.8/gems/rake-0.9.2.2/lib/rake/application.rb:133:in `standard_exception_handling'
/var/lib/gems/1.8/gems/rake-0.9.2.2/lib/rake/application.rb:88:in `top_level'
/var/lib/gems/1.8/gems/rake-0.9.2.2/lib/rake/application.rb:66:in `run'
/var/lib/gems/1.8/gems/rake-0.9.2.2/lib/rake/application.rb:133:in `standard_exception_handling'
/var/lib/gems/1.8/gems/rake-0.9.2.2/lib/rake/application.rb:63:in `run'
/var/lib/gems/1.8/gems/rake-0.9.2.2/bin/rake:33
/var/lib/gems/1.8/bin/rake:19:in `load'
/var/lib/gems/1.8/bin/rake:19
Tasks: TOP => redmine:email:receive_imap
```

# History

# #1 - 2012-06-18 15:12 - Arnis Juraga

- File attachedtextfile.txt added

#### #2 - 2012-06-18 17:11 - Jean-Philippe Lang

Please, attach the full raw email that contains this attachment and give your exact Ruby and Redmine versions.

#### #3 - 2012-06-19 16:59 - Arnis Juraga

Redmine version: == 2012-06-05 v2.0.2

```
~# ruby -v
ruby 1.8.7 (2010-08-16 patchlevel 302) [x86_64-linux]
```

Today I had another incoming email, which broke email subject. I noticed, that on some e-mail clients issue subject was readable, but with different encoding.

In message source Subject was set to: =?UTF-8?Q?[\*\_ien=C4=81ko=C5=A1ie\_e-pasti]\_#287\_-\_Apm=E2c=EEbu?==?UTF-8?Q?\_materi=E2ls\_darbam\_ar\_jauno\_webserveri?=

Anyway - another task with incoming attachemtn

Rake task result (notice warning: Non US-ASCII detected and no charset defined.

Defaulting to UTF-8, set your own if this is incorrect.):

```
** Invoke redmine:email:receive_imap (first_time)
** Invoke environment (first_time)
** Execute environment
** Execute redmine:email:receive_imap
Non US-ASCII detected and no charset defined.
Defaulting to UTF-8, set your own if this is incorrect.
rake aborted!
"šrutu apraksti \r"...
/var/lib/gems/1.8/gems/mail-2.4.4/lib/mail/message.rb:2046:in `conv'
/var/lib/gems/1.8/gems/mail-2.4.4/lib/mail/message.rb:2046:in `decode_body_as_te
                                                                    xt'
/var/lib/gems/1.8/gems/mail-2.4.4/lib/mail/message.rb:1786:in `decoded'
/opt/redmine/redmine-2.0.2/app/models/mail_handler.rb:245:in `add_attachments'
/opt/redmine/redmine-2.0.2/app/models/mail_handler.rb:243:in `each'
/opt/redmine/redmine-2.0.2/app/models/mail_handler.rb:243:in `add_attachments'
/opt/redmine/redmine-2.0.2/app/models/mail_handler.rb:175:in `receive_issue'
/opt/redmine/redmine-2.0.2/app/models/mail_handler.rb:152:in `dispatch_to_defaul
/opt/redmine/redmine-2.0.2/app/models/mail_handler.rb:137:in `dispatch'
/opt/redmine/redmine-2.0.2/app/models/mail_handler.rb:113:in `receive'
/var/lib/gems/1.8/gems/actionmailer-3.2.5/lib/action_mailer/base.rb:404:in `rece
/var/lib/gems/1.8/gems/activesupport-3.2.5/lib/active_support/notifications.rb:1
                                                                    23:in `instrument'
/var/lib/gems/1.8/gems/activesupport-3.2.5/lib/active_support/notifications/inst
                                                                   rumenter.rb:20:in `instrument'
/var/lib/gems/1.8/gems/activesupport-3.2.5/lib/active_support/notifications.rb:1
                                                                   23:in `instrument'
/var/lib/gems/1.8/gems/actionmailer-3.2.5/lib/action_mailer/base.rb:401:in `rece
```

2025-05-01 2/8

```
/opt/redmine/redmine-2.0.2/app/models/mail_handler.rb:44:in `receive'
/opt/redmine/redmine-2.0.2/lib/redmine/imap.rb:35:in `check'
/opt/redmine/redmine-2.0.2/lib/redmine/imap.rb:32:in `each'
/opt/redmine/redmine-2.0.2/lib/redmine/imap.rb:32:in `check'
/opt/redmine/redmine-2.0.2/lib/tasks/email.rake:133
/var/lib/gems/1.8/gems/rake-0.9.2.2/lib/rake/task.rb:205:in `call'
/var/lib/gems/1.8/gems/rake-0.9.2.2/lib/rake/task.rb:205:in `execute'
/var/lib/gems/1.8/gems/rake-0.9.2.2/lib/rake/task.rb:200:in `each'
/var/lib/gems/1.8/gems/rake-0.9.2.2/lib/rake/task.rb:200:in
/var/lib/gems/1.8/gems/rake-0.9.2.2/lib/rake/task.rb:158:in `invoke_with_call_ch
/usr/lib/ruby/1.8/monitor.rb:242:in `synchronize'
/var/lib/gems/1.8/gems/rake-0.9.2.2/lib/rake/task.rb:151:in `invoke_with_call_ch
/var/lib/gems/1.8/gems/rake-0.9.2.2/lib/rake/task.rb:144:in `invoke'
/var/lib/gems/1.8/gems/rake-0.9.2.2/lib/rake/application.rb:116:in `invoke_task'
/var/lib/gems/1.8/gems/rake-0.9.2.2/lib/rake/application.rb:94:in `top_level'
/var/lib/gems/1.8/gems/rake-0.9.2.2/lib/rake/application.rb:94:in `each'
/var/lib/gems/1.8/gems/rake-0.9.2.2/lib/rake/application.rb:94:in `top_level'
/var/lib/gems/1.8/gems/rake-0.9.2.2/lib/rake/application.rb:133:in `standard_exc
/var/lib/gems/1.8/gems/rake-0.9.2.2/lib/rake/application.rb:88:in `top_level'
/var/lib/gems/1.8/gems/rake-0.9.2.2/lib/rake/application.rb:66:in `run'
/var/lib/gems/1.8/gems/rake-0.9.2.2/lib/rake/application.rb:133:in `standard_exc
/var/lib/gems/1.8/gems/rake-0.9.2.2/lib/rake/application.rb:63:in `run'
/var/lib/gems/1.8/gems/rake-0.9.2.2/bin/rake:33
/var/lib/gems/1.8/bin/rake:19:in `load'
/var/lib/gems/1.8/bin/rake:19
Tasks: TOP => redmine:email:receive_imap
Message source
Delivered-To: support@***OURDOMAIN***
Received: by 10.68.21.38 with SMTP id s6csp293641pbe;
       Tue, 19 Jun 2012 07:47:22 -0700 (PDT)
Received: by 10.204.145.89 with SMTP id c25mr8626763bkv.5.1340117241694;
       Tue, 19 Jun 2012 07:47:21 -0700 (PDT)
Return-Path: <arnis@***OURDOMAIN*** >
Received: from mail-bk0-f52.google.com (mail-bk0-f52.google.com [IPADDRESS])
        by mx.google.com with ESMTPS id hyl5sil5537481bkc.22.2012.06.19.07.47.20
        (version=TLSv1/SSLv3 cipher=OTHER);
       Tue, 19 Jun 2012 07:47:21 -0700 (PDT)
Received-SPF: neutral (google.com: IPADDRESS is neither permitted nor denied by best guess record for domain o
f arnis@***OURDOMAIN***) client-ip=***OURDOMAIN***;
Authentication-Results: mx.google.com; spf=neutral (google.com: ***OURDOMAIN*** is neither permitted nor denie
d by best guess record for domain of arnis@***OURDOMAIN***) smtp.mail=arnis@***OURDOMAIN**
Received: by bkcjc3 with SMTP id jc3so6049822bkc.11
        for <support@***OURDOMAIN***>; Tue, 19 Jun 2012 07:47:20 -0700 (PDT)
X-Google-DKIM-Signature: v=1; a=rsa-sha256; c=relaxed/relaxed;
        d=google.com; s=20120113;
        h=message-id:date:from:user-agent:mime-version:to:subject
         :content-type:x-gm-message-state;
        bh=PgwfJNVBaPo4u5uWl09nBLc/uIMfI3YZuOPe3LzMKiw=;
        b = \texttt{IJ2OYVqU8} \\ no \texttt{5TDGTqnKusBNqDT5gdL5kOse57Cu5HTM813hxsHiQWYd4IXafVbQ+WJ} \\
         a2kgnuUh3BgqIHeEmT7bTLfXfy7CnyTTLgILjFi3iCJi9QXSVSKrjiaulEM5gwFX47xs
         {\tt P0c7vHI4m+PDkgPtbgj9DMRjqRiRigZ1S8LOVduEt3NJAfrCceecDqnEiJ1V405HBSlp}
         CUz134p5LzS6GULkHtzR0dI9A4v0eHVSXkHfqrjFoFYetroz20sfuXt2K2h2c59Idk34
         9gpf5+J+0g9xmTW5ik2a1u75L/rLVLS19ONjxsHWMMWA973Og3Us90dx93BKRdLQxVfb
Received: by 10.204.128.201 with SMTP id 19mr8468091bks.68.1340117240493;
       Tue, 19 Jun 2012 07:47:20 -0700 (PDT)
Return-Path: <arnis@***OURDOMAIN***>
Received: from [192.168.1.101] ([***OURDOMAIN***])
       by mx.google.com with ESMTPS id u8sm23640286bks.0.2012.06.19.07.47.18
        (version=SSLv3 cipher=OTHER);
        Tue, 19 Jun 2012 07:47:19 -0700 (PDT)
Message-ID: <4FE090F1.8020307@***OURDOMAIN***>
Date: Tue, 19 Jun 2012 17:47:13 +0300
From: Arnis Juraga <arnis@***OURDOMAIN***>
User-Agent: Postbox 3.0.3 (Windows/20120304)
MIME-Version: 1.0
To: Support Desk <support@***OURDOMAIN***>
```

2025-05-01 3/8

```
Subject: =?UTF-8?B?TWFyxaFydXR1IGFwcmFrc3Rp?=
Content-Type: multipart/mixed;
boundary="----090206070609080307050305"
X-Gm-Message-State: ALoCoQlJdbjyt4PqpQW81U4Ygmz18ItlnPoDs9v5/TRKDIBSWkJ7DaVb7Q1WZ4J/d0r16/y9qbg8
This is a multi-part message in MIME format.
    ----090206070609080307050305
Content-Type: text/plain; charset=UTF-8
Content-Transfer-Encoding: 8bit
test vs "maršrutu apraksti".
Arnis
 -----090206070609080307050305
Content-Type: text/plain;
name="attachedtextfile.txt"
Content-Transfer-Encoding: base64
Content-Disposition: attachment;
 filename="attachedtextfile.txt"
MikgbWFy8HJ1dHUgYXByYWtzdGkgDQoNCg0KDQoNCiA=
-----090206070609080307050305--
```

#### #4 - 2012-06-28 11:42 - Arnis Juraga

Still, the same problems!

I can see, there are some problems with encoding, charsets?

When e-mail has been read, the message Subject, for example, is incorrectly rewritten. I can see in Message source:

```
ORIGINAL MESSAGE AS ON MAIL SERVER:
Subject: =?windows-1257?Q?sinhroniz=E2cija?=

Email, sent by REDMINE:
Subject: =?UTF-8?Q?[*_ien=C4=81ko=C5=A1ie_e-pasti]_#266_-_sinhroniz=E2cija?=
```

Can it be fixed in config files?

# #5 - 2012-06-28 11:44 - Arnis Juraga

Also, after incoming email has been read in, Redmine saves "truncated" message suject, for example: Incoming message with subject: "sinhronizācija" is created as issue with subject: "sinhroniz"

# #6 - 2012-06-28 13:47 - Andre Rodier

I confirm that I have the same issue.

My email contain my name (André) in the signature, and the imap importation fail:

```
Gem.source_index called from /usr/share/redmine/vendor/rails/railties/lib/rails/gem_dependency.rb:21.
** Invoke redmine:email:receive_imap (first_time)
** Invoke environment (first_time)
** Execute environment
** Execute redmine:email:receive_imap
rake aborted!
incompatible encoding regexp match (ASCII-8BIT regexp with UTF-8 string)
/usr/share/redmine/app/models/mail_handler.rb:421:in `gsub'
/usr/share/redmine/app/models/mail_handler.rb:421:in `cleanup_body'
/usr/share/redmine/app/models/mail_handler.rb:359:in `cleaned_up_text_body'
/usr/share/redmine/app/models/mail_handler.rb:192:in `receive_issue_reply'
/usr/share/redmine/app/models/mail_handler.rb:205:in `receive_journal_reply'
/usr/share/redmine/app/models/mail_handler.rb:122:in `dispatch' /usr/share/redmine/app/models/mail_handler.rb:107:in `receive'
/usr/lib/ruby/vendor_ruby/action_mailer/base.rb:452:in `receive'
/usr/share/redmine/app/models/mail_handler.rb:42:in `receive'
/usr/share/redmine/lib/redmine/imap.rb:35:in `block in check'
/usr/share/redmine/lib/redmine/imap.rb:32:in `each'
/usr/share/redmine/lib/redmine/imap.rb:32:in `check'
/usr/share/redmine/lib/tasks/email.rake:133:in `block (3 levels) in <top (required)>'
/usr/lib/ruby/vendor_ruby/rake/task.rb:205:in `call'
/usr/lib/ruby/vendor_ruby/rake/task.rb:205:in `block in execute'
/usr/lib/ruby/vendor_ruby/rake/task.rb:200:in
/usr/lib/ruby/vendor_ruby/rake/task.rb:200:in `execute'
```

2025-05-01 4/8

```
/usr/lib/ruby/vendor_ruby/rake/task.rb:158:in `block in invoke_with_call_chain'
/usr/lib/ruby/1.9.1/monitor.rb:211:in `mon_synchronize'
/usr/lib/ruby/vendor_ruby/rake/task.rb:151:in `invoke_with_call_chain'
/usr/lib/ruby/vendor_ruby/rake/task.rb:144:in `invoke'
/usr/lib/ruby/vendor_ruby/rake/application.rb:116:in `invoke_task'
/usr/lib/ruby/vendor_ruby/rake/application.rb:94:in `block (2 levels) in top_level'
/usr/lib/ruby/vendor_ruby/rake/application.rb:94:in `block in top_level'
/usr/lib/ruby/vendor_ruby/rake/application.rb:94:in `block in top_level'
/usr/lib/ruby/vendor_ruby/rake/application.rb:133:in `standard_exception_handling'
/usr/lib/ruby/vendor_ruby/rake/application.rb:66:in `block in run'
/usr/lib/ruby/vendor_ruby/rake/application.rb:133:in `standard_exception_handling'
/usr/lib/ruby/vendor_ruby/rake/application.rb:63:in `run'
/usr/bin/rake:27:in `<main>'
Tasks: TOP => redmine:email:receive_imap
```

However, if I remove my name, it's working...

#### #7 - 2012-08-14 04:41 - Bjarni Thorisson

I have the same problem.

To reproduce, log into a gmail account. Go to settings, on the first tab (General) make sure the "Outgoing message encoding" is set to "Use default text encoding for outgoing messages"

Then send an email containing non ASCII letters, for example ú æ í þ ð.

It will not turn into a ticket, the error I get is:

```
_____
```

```
rake aborted!
```

PG::Error: ERROR: invalid byte sequence for encoding "UTF8": 0xe16c70
: INSERT INTO "issues" ("assigned\_to\_id", "author\_id", "category\_id", "created\_on", "description", "done\_ratio", "due\_date", "estimated\_hours", "fixed\_version\_id", "is\_private", "lft", "lock\_version", "parent\_id", "priority\_id", "project\_id", "rgt", "root\_id", "start\_date", "status\_id", "subject", "tracker\_id", "updated\_on") VALUES (\$1, \$2, \$3, \$4, \$5, \$6, \$7, \$8, \$9, \$10, \$11, \$12, \$13, \$14, \$15, \$16, \$17, \$18, \$19, \$20, \$21, \$22)
RETURNING "id"

-----

If you then try setting the "Outgoing message encoding" to utf8 it works again.

This obviously means I can only accept email from people with their email client set to utf8, if they use special characters.

### #8 - 2012-08-14 05:26 - Bjarni Thorisson

I fixed it, this only blew up if the subject contained special characters.

in mail\_handler.rb I changed the receive\_issue function:

```
def receive_issue
   project = target_project
   # check permission
   unless @@handler_options[:no_permission_check]
    raise UnauthorizedAction unless user.allowed_to?(:add_issues, project)
   end
   issue = Issue.new(:author => user, :project => project)
   issue.safe_attributes = issue_attributes_from_keywords(issue)
issue.safe_attributes = {'custom_field_values' => custom_field_values_from_keywords(issue)}
   # CHANGED THE FOLLOWING FOUR LINES:
   body_part = email.text_part || email.html_part || email
   subj = email.subject
   subj = Redmine::CodesetUtil.to_utf8(subj, body_part.charset)
  issue.subject = subj.chomp[0,255]
  if issue.subject.blank?
     issue.subject = '(no subject)'
   end
issue.description = cleaned_up_text_body
# add To and Cc as watchers before saving so the watchers can reply to Redmine
   add_watchers(issue)
   issue.save!
   add attachments(issue)
   logger.info "MailHandler: issue ##{issue.id} created by #{user}" if logger && logger.info
```

2025-05-01 5/8

As I am not a ruby programmer I'm sure this could be done in a more elegant way. The main thing is to make sure that the subject is also converted to utf8, you can check its' current encoding by checking the encoding of the body.

#### #9 - 2012-08-14 05:28 - Bjarni Thorisson

BTW: I'm guessing something similar has to be done for txt attachments

#### #10 - 2013-04-16 15:22 - Steffen Zieger

Any news on this? I'm running into this issue currently.

Redmine version 2.3.0

# #11 - 2013-04-16 15:38 - Steffen Zieger

- File redmine\_mail\_receive.diff added

The attached patch fixes this issue for me and is tested against Redmine 2.3.0

#### #12 - 2013-04-17 06:00 - Toshi MARUYAMA

Steffen Zieger wrote:

The attached patch fixes this issue for me and is tested against Redmine 2.3.0

Could you add tests?

See:

- source:tags/2.3.0/test/unit/mail\_handler\_test.rb#L495
- source:tags/2.3.0/test/fixtures/mail handler/subject as iso-8859-1.eml

# #13 - 2013-06-03 16:37 - Steffen Zieger

- File redmine\_attachment\_charset\_issue.diff added

Toshi MARUYAMA wrote:

Could you add tests?

As time is problematic right now, I can't promise it, but I'll do my best.

Attached is a patch, which fixes this issue in attachments, too. Maybe there is a better way, but at least it's working for me.

# #14 - 2013-06-04 01:06 - Toshi MARUYAMA

- Category set to Email receiving

# #15 - 2013-08-27 11:12 - Bernd Köster

Are there any reasons that these patches are not set for the 2.3.3 version? Can I help out?

# #16 - 2013-09-04 05:45 - Toshi MARUYAMA

Bernd Köster wrote:

Are there any reasons that these patches are not set for the 2.3.3 version?

Because this issue patches have no tests.

# #17 - 2013-11-07 14:15 - Arnis Juraga

And still - problem persists in the latest Redmine version as well.

Can I do tests, to verify fix?

# #18 - 2014-11-21 14:53 - Aníbal Pacheco

2025-05-01 6/8

#### #19 - 2014-11-21 17:39 - Arnis Juraga

Look at mine Redmine/Rails/Gems version, may be upgrade can help for You?

I cannot reproduce it today anymore, with the same old file I have attached myself,

#### Imap read script:

```
#!/bin/bash
export GEM_HOME=/var/lib/gems/1.9.1/gems/
export PATH=/var/lib/gems/1.9.1/bin:$PATH
RAILS_ENV=production
dirpath="/opt/redmine/redmine-ri-2.6.0"
cd $dirpath
```

/usr/local/bin/rake -f \$dirpath/Rakefile redmine:email:receive\_imap RAILS\_ENV="production" host=imap.gmail.com ssl=SSL \

port=993 username=support@DOMAIN password=PASSWORD move\_on\_success=izlasitie \

#### Email was received and added to Redmine correctly now!!!

#### And received ouput:

```
** Invoke redmine:email:receive_imap (first_time)

** Invoke environment (first_time)

** Execute environment

** Execute redmine:email:receive_imap

Non US-ASCII detected and no charset defined.

Defaulting to UTF-8, set your own if this is incorrect.

Non US-ASCII detected and no charset defined.

Defaulting to UTF-8, set your own if this is incorrect.

Non US-ASCII detected and no charset defined.

Defaulting to UTF-8, set your own if this is incorrect.
```

# As You can see, IMAP read scripts uses gems 1.9.1, but the Redmine version itself is as follows:

# Environment:

```
2.6.0.stable
 Redmine version
                               1.9.3-p194 (2012-04-20) [i486-linux]
 Ruby version
 Rails version
                               3.2.19
 Environment
                               production
 Database adapter
                               Mysq12
SCM:
 Subversion
                               1.6.17
 Mercurial
                               2.2.2
                               1.7.10.4
 Git
 Filesystem
Redmine plugins:
                     0.0.1
 add_link
                            1.0.0
 progressive_projects_list
 redmine_agile
                               1.3.5
 redmine_changeauthor
                               1.0.0
                               3.0.1
 redmine checklists
 redmine_custom_css
                              0.1.4
 redmine_github_hook
                               2.1.0
 redmine_helpdesk
                               0.0.8
 redmine_image_clipboard_paste 1.0.0
 redmine_lightbox2
                               0.0.3
 redmine_planning
                               0.7.6
 redmine_slack
```

# #20 - 2019-02-09 08:29 - Go MAEDA

- Status changed from New to Closed
- Resolution set to Cant reproduce

I cannot reproduce the problem with the raw message attached in #11191#note-3 in Redmine 4.0.1.devel.17851. An issue was successfully created and the Russian subject was not broken.

Maybe something was fixed in some version of Mail gem.

2025-05-01 7/8

# #21 - 2022-02-02 20:00 - Daniel DrexImaier

ERROR --: MailHandler: an unexpected error occurred when receiving email: Mysql2::Error: Incorrect string value: '\xF0\x9F\x94\xA5 S...' for column `xxx`.`issues`.`description` at row 1: INSERT INTO `issues` (`tracker\_id`, `project\_id`, `subject`, `description`, `status\_id`, `assigned\_to\_id`, `priority\_id`, `author\_id`, `created\_on`, `updated\_on`, `start\_date`, `lock\_version`) VALUES

REASON: utf8mb -> Unicode Symbols

# #22 - 2022-02-02 21:15 - Daniel DrexImaier

Solution: Convert table to utf8mb and set in file database.yml "encoding: utf8mb4"

# **Files**

attachedtextfile.txt	32 Bytes	2012-06-18	Arnis Juraga
redmine_mail_receive.diff	487 Bytes	2013-04-16	Steffen Zieger
redmine_attachment_charset_issue.diff	1.69 KB	2013-06-03	Steffen Zieger

2025-05-01 8/8