## Redmine - Defect #11749

# Redmine.pm: HEAD is not considered as a read-only method

2012-08-31 12:13 - Antonio García-Domínguez

Status: Closed Start date:

Priority: Normal Due date:

Assignee: Jean-Philippe Lang % Done: 0%

Category: SCM extra Estimated time: 0.00 hour

Resolution: Fixed Affected version: 2.0.3

## **Description**

Target version:

I've been using Redmine.pm to control access to other per-project resources that aren't really repositories, such as WebDAV storage areas. One of these WebDAV areas hosted an Eclipse repository in a public project, and it was asking for a password simply to install artifacts from it from Eclipse.

After looking at the logs, it appears that Eclipse was checking if a certain file existed using the HTTP HEAD method. As it's not considered read-only by Redmine.pm, it was asking for auth credentials. IIRC, HTTP HEAD is a read-only method, as it is basically a GET request without the body:

http://www.w3.org/Protocols/rfc2616/rfc2616-sec9.html#sec9.4

2.1.0

I've attached a trivial patch that fixes the problem by adding HEAD as a read-only method. With this, the hosted update site can be installed from Eclipse just fine.

#### **Associated revisions**

### Revision 10279 - 2012-09-02 14:59 - Jean-Philippe Lang

Redmine.pm: HEAD is not considered as a read-only method (#11749).

#### History

### #1 - 2012-08-31 12:21 - Toshi MARUYAMA

- Category set to SCM extra

# #2 - 2012-09-01 14:53 - Jean-Philippe Lang

- Target version set to 2.1.0

### #3 - 2012-09-02 14:59 - Jean-Philippe Lang

- Status changed from New to Closed
- Assignee set to Jean-Philippe Lang
- Resolution set to Fixed

Committed in r10279.

#### **Files**

add-head-as-read-only.patch 759 Bytes 2012-08-31 Antonio García-Domínguez

2025-05-17 1/1