

Redmine - Defect #13510

async\_smtp isn't working for gmail

2013-03-18 15:56 - Jianrong SUN

Status:	Closed	Start date:	
Priority:	Normal	Due date:	
Assignee:		% Done:	0%
Category:	Email notifications	Estimated time:	0.00 hour
Target version:		Affected version:	2.2.2
Resolution:	Invalid		

Description

Here is my configuration.yml about mail settings:

```
production:
  email_delivery:
    delivery_method: :async_smtp
    #delivery_method: :smtp
    smtp_settings:
      #tls: true
      enable_starttls_auto: true
      address: "smtp.gmail.com"
      port: 587
      domain: "test.com" # 'your.domain.com' for GoogleApps
      authentication: :plain
      user_name: "admin@test.com"
      password: "test"
```

When the delivery\_method change to :smtp, everything works fine. But when using async\_smtp, it returns:

```
>rake redmine:email:test[test] RAILS_ENV=production
Setting Load (1.5ms)  SELECT `settings`.* FROM `settings` WHERE `settings`.`name` = 'sequential_
project_identifiers' LIMIT 1
Setting Load (0.1ms)  SELECT `settings`.* FROM `settings` WHERE `settings`.`name` = 'default_pro
jects_public' LIMIT 1
Setting Load (0.1ms)  SELECT `settings`.* FROM `settings` WHERE `settings`.`name` = 'default_pro
jects_modules' LIMIT 1
Tracker Load (0.1ms)  SELECT `trackers`.* FROM `trackers` ORDER BY trackers.position ASC
Setting Load (0.1ms)  SELECT `settings`.* FROM `settings` WHERE `settings`.`name` = 'plugin_redm
ine_git_hosting' LIMIT 1
User Load (0.1ms)     SELECT `users`.* FROM `users` WHERE `users`.`type` IN ('User', 'AnonymousUser
') AND `users`.`login` = 'test'
Setting Load (0.2ms)  SELECT `settings`.* FROM `settings` WHERE `settings`.`name` = 'default_lan
guage' LIMIT 1
Setting Load (0.2ms)  SELECT `settings`.* FROM `settings` WHERE `settings`.`name` = 'host_name'
LIMIT 1
Setting Load (0.1ms)  SELECT `settings`.* FROM `settings` WHERE `settings`.`name` = 'protocol' L
IMIT 1
Setting Load (0.1ms)  SELECT `settings`.* FROM `settings` WHERE `settings`.`name` = 'app_title'
LIMIT 1
Setting Load (0.1ms)  SELECT `settings`.* FROM `settings` WHERE `settings`.`name` = 'mail_from'
LIMIT 1
Setting Load (0.1ms)  SELECT `settings`.* FROM `settings` WHERE `settings`.`name` = 'bcc_recipie
nts' LIMIT 1
Setting Load (0.1ms)  SELECT `settings`.* FROM `settings` WHERE `settings`.`name` = 'emails_head
er' LIMIT 1
Setting Load (0.1ms)  SELECT `settings`.* FROM `settings` WHERE `settings`.`name` = 'emails_foot
er' LIMIT 1
Setting Load (0.1ms)  SELECT `settings`.* FROM `settings` WHERE `settings`.`name` = 'plain_text_
mail' LIMIT 1
Setting Load (0.1ms)  SELECT `settings`.* FROM `settings` WHERE `settings`.`name` = 'text_format
ting' LIMIT 1
Setting Load (0.1ms)  SELECT `settings`.* FROM `settings` WHERE `settings`.`name` = 'cache_forma
```

```
tted_text' LIMIT 1
```

```
An error occurred while sending mail (Connection refused - connect(2))
```

## History

---

### #1 - 2013-03-18 16:49 - Etienne Massip

- *Status changed from New to Needs feedback*

I think you have to use `async_smtp_settings` instead of `smtp_settings`.

### #2 - 2013-03-18 19:34 - Etienne Massip

- *Status changed from Needs feedback to Closed*

- *Resolution set to Invalid*