

Redmine - Defect #157

URLs in emails do not use HTTPS when appropriate

2007-11-30 09:31 - Mike Dalessio

Status: Closed	Start date:
Priority: Normal	Due date:
Assignee:	% Done: 0%
Category:	Estimated time: 0.00 hour
Target version:	Affected version:
Resolution:	

Description

My redmine installation is set up on an HTTPS site, so my team accesses via <https://x.y.com/redmine/>

When issues are created or updated, the emails don't use <https://...> they use <http://>.

for example, text emails look like:

```
Issue #31 has been reported.
-----
Feature #31: My Problem Is
http://x.y.com/redmine/issues/show/31
```

and the html emails look like:

```
Issue #31 has been reported.
<hr />
<a href="http://x.y.com/redmine/issues/show/31">Feature #31</a>:
My Problem Is
```

I believe this may be due to the use of `url_for` in views. According to the ActionMailer docs:

```
If your view includes URLs from the application, you need to use url_for in the mailing method instead of the view.
Unlike controllers from Action Pack, the mailer instance doesn't have any context about the incoming request. That's why you need to jump this little hoop and supply all the details needed for the URL.
```

History

#1 - 2007-12-01 12:26 - Jean-Philippe Lang

I don't know which version/revision you're using but this problem was solved in [r877](#) and thus in 0.6.0.

There's now a 'Protocol' setting in admin -> settings that lets you choose if generated urls should use http or https.

If you set this setting to 'https', all links in emails will use https instead of http.