

Redmine - Feature #16930

Need Additional parameter for hook to enable Multi Factor Authentication Patch

2014-05-20 11:28 - Mani Malekmohammadi

Status:Closed

Priority:Normal

Assignee:Jean-Philippe Lang

Category:Hook requests

Target version:

Resolution:Wont fix

Start date:

Due date:

% Done:0%

Estimated time:0.00 hour

Description

I developed a plugin for one of our clients in order to enable multi factor Authentication for their Redmine users, here is the plugin:
<https://github.com/acceptto-corp/acceptto-mfa-redmine-plugin>
In order to enable multi factor login after login we redirect users to another page waiting to accept login on his/her device in a mobile application. for redirecting to another page after login I need to have access to params in Account_controller:


```
diff --git a/app/controllers/account_controller.rb b/app/controllers/account_controller.rb
index ed38eea..4762d64 100644
--- a/app/controllers/account_controller.rb
+++ b/app/controllers/account_controller.rb
@@ -255,7 +255,7 @@ class AccountController < ApplicationController
   if params[:autologin] && Setting.autologin?
     set_autologin_cookie(user)
   end
-  call_hook(:controller_account_success_authentication_after, {:user => user })
+  call_hook(:controller_account_success_authentication_after, {:user => user, :params => params
})
  redirect_back_or_default my_page_path
end
```


--
1.8.4

Is it possible to include 'param' in hook parameters? I don't want to patch anything and just use plugin for easier upgrades.

Associated revisions

Revision 13394 - 2014-09-13 13:09 - Jean-Philippe Lang

Adds a test for default context of controller hooks (#16930).

History

#1 - 2014-05-20 14:19 - Mani Malekmohammadi

@From a303e0c0c7f60d0387dc781f79dc0ed1ff04fc5c Mon Sep 17 00:00:00 2001
From: mani47 <mm.mani@gmail.com>
Date: Sat, 17 May 2014 18:27:38 +0430
Subject: [PATCH] patching redmine to enable mfa

app/controllers/account_controller.rb | 2 +-
1 file changed, 1 insertions(+), 1 deletion(-)

diff --git a/app/controllers/account_controller.rb b/app/controllers/account_controller.rb
index ed38eea..4762d64 100644
--- a/app/controllers/account_controller.rb
+++ b/app/controllers/account_controller.rb
@@ -255,7 +255,7 @@ class AccountController < ApplicationController
 if params[:autologin] && Setting.autologin?
 set_autologin_cookie(user)
 end
- call_hook(:controller_account_success_authentication_after, {:user => user })
+ call_hook(:controller_account_success_authentication_after, {:user => user, :params => params})
 redirect_back_or_default my_page_path
end

--
1.8.4
@

#2 - 2014-05-24 14:00 - Jean-Philippe Lang

- *Target version set to 2.6.0*

#3 - 2014-06-18 07:35 - Toshi MARUYAMA

- *Description updated*

#4 - 2014-09-13 13:12 - Jean-Philippe Lang

- *Status changed from New to Closed*

- *Assignee set to Jean-Philippe Lang*

- *Target version deleted (2.6.0)*

- *Resolution set to Wont fix*

Actually, adding `:params` to the context of controller hooks is not needed. The request is automatically added to the context of these hooks (see: [source:/tags/2.5.0/lib/redmine/hooks.rb#L149](https://github.com/redmine/redmine/blob/2.5.0/lib/redmine/hooks.rb#L149)).

You can use `context[:request].params` in your hook to access the params (test added in [r13394](#)).