

Redmine - Patch #1782

Unit tests fail when using a Git clone of the original SVN repository

2008-08-13 16:07 - Simone Carletti

Status: Closed	Start date: 2008-08-13
Priority: Normal	Due date:
Assignee:	% Done: 0%
Category: SCM	Estimated time: 0.00 hour
Target version:	
Description This patch add compatibility with Git clones of the original SVN repository. Because Git doesn't store empty folders, you should use mkpath instead of mkdir when parent folder could be empty.	

History

#1 - 2008-08-13 17:37 - Eric Davis

I'm not sure if this is relevant but the testing documentation states:

```
Creating test repositories
```

```
=====
```

```
mkdir tmp/test
```

```
....
```

Found in doc/RUNNING_TESTS

#2 - 2008-08-13 18:39 - Simone Carletti

Eric Davis wrote:

I'm not sure if this is relevant but the testing documentation states:

```
Creating test repositories
```

```
=====
```

```
mkdir tmp/test
```

```
....
```

Found in doc/RUNNING_TESTS

Hi Eric,

I admin I didn't realized there was a test documentation in doc folder before you pointed it out.

If you create /tmp/test folder you should probably be safe unless tmp is empty. If so, you should create tmp before.

#3 - 2011-01-24 01:41 - Toshi MARUYAMA

- Category set to SCM

- Assignee deleted (Jean-Philippe Lang)

#4 - 2011-02-02 03:31 - Toshi MARUYAMA

- Status changed from New to Closed

tmp/test/empty is added at [r2784](#).

Files

patch_for_running_tests_with_git.patch

791 Bytes

2008-08-13

Simone Carletti