

Redmine - Defect #21596

internal error when click register or project setting tab after redmine fresh installation

2015-12-23 15:25 - Tony Cao

Status:	Closed	Start date:	
Priority:	Normal	Due date:	
Assignee:		% Done:	0%
Category:	Database	Estimated time:	0.00 hour
Target version:		Affected version:	2.6.0
Resolution:	Invalid		
Description			
Log is pasted as below. ===== [root@redmine01 redmine-2.6]# RAILS_ENV=production bundle exec rake redmine:load_default_data /usr/local/rvm/gems/ruby-2.2.4/gems/htmlentities-4.3.1/lib/htmlentities/mappings/expanded.rb:465: warning: duplicated key at line 466 ignored: "inodot"			
Select language: ar, az, bg, bs, ca, cs, da, de, el, en, en-GB, es, et, eu, fa, fi, fr, gl, he, hr, hu, id, it, ja, ko, lt, lv, mk, mn, nl, no, pl, pt, pt-BR, ro, ru, sk, sl, sq, sr, sr-YU, sv, th, tr, uk, vi, zh, zh-TW [en] en ===== Default configuration data loaded. [root@redmine01 redmine-2.6]# mysql -u root -p Enter password: Welcome to the MySQL monitor. Commands end with ; or \g. Your MySQL connection id is 27 Server version: 5.6.28 MySQL Community Server (GPL) Copyright (c) 2000, 2015, Oracle and/or its affiliates. All rights reserved. Oracle is a registered trademark of Oracle Corporation and/or its affiliates. Other names may be trademarks of their respective owners. Type 'help;' or '\h' for help. Type '\c' to clear the current input statement. mysql> use redmine2; Reading table information for completion of table and column names You can turn off this feature to get a quicker startup with -A Database changed mysql> select * from settings; Empty set (0.00 sec) mysql> =====			
I wonder if load default data is working fine, because there is no default data in settings table.			

History

#1 - 2015-12-23 15:31 - Tony Cao

Tony Cao wrote:

Log is pasted as below. =====
[root@redmine01 redmine-2.6]# RAILS_ENV=production bundle exec rake redmine:load_default_data
/usr/local/rvm/gems/ruby-2.2.4/gems/htmlentities-4.3.1/lib/htmlentities/mappings/expanded.rb:465: warning: duplicated key at line 466 ignored: "inodot"

Select language: ar, az, bg, bs, ca, cs, da, de, el, en, en-GB, es, et, eu, fa, fi, fr, gl, he, hr, hu, id, it, ja, ko, lt, lv, mk, mn, nl, no, pl, pt, pt-BR, ro, ru, sk, sl, sq, sr, sr-YU, sv, th, tr, uk, vi, zh, zh-TW [en] en =====
Default configuration data loaded.
[root@redmine01 redmine-2.6]# mysql -u root -p
Enter password:
Welcome to the MySQL monitor. Commands end with ; or \g.
Your MySQL connection id is 27

Server version: 5.6.28 MySQL Community Server (GPL)

Copyright (c) 2000, 2015, Oracle and/or its affiliates. All rights reserved.

Oracle is a registered trademark of Oracle Corporation and/or its affiliates. Other names may be trademarks of their respective owners.

Type 'help;' or 'h' for help. Type 'c' to clear the current input statement.

```
mysql> use redmine2;
```

Reading table information for completion of table and column names

You can turn off this feature to get a quicker startup with -A

Database changed

```
mysql> select * from settings;
```

Empty set (0.00 sec)

```
mysql>
```

=====

I wonder if load default data is working fine, because there is no default data in settings table.

I added my database config and creating database log as follows:

```
[root@redmine01 config]# cat database.yml
```

1. Default setup is given for MySQL with ruby1.9. If you're running Redmine
2. with MySQL and ruby1.8, replace the adapter name with `mysql`.
3. Examples for PostgreSQL, SQLite3 and SQL Server can be found at the end.
4. Line indentation must be 2 spaces (no tabs).

production:

adapter: mysql2

database: redmine2

host: localhost

username: redmine

password: "redmine"

encoding: utf8

```
mysql> create database redmine2 character set utf8;
```

```
mysql> grant all privileges on redmine2.* to 'redmine'@'localhost' identified by 'redmine';
```

```
mysql> flush privileges;
```

```
mysql> \q
```

#2 - 2015-12-23 16:07 - Toshi MARUYAMA

- *Status changed from New to Closed*

- *Resolution set to Invalid*

Please use forum for question.