## Redmine - Defect #21682

# Documentation for nginx configuration is outdated and broken

2016-01-08 19:45 - Erik H

Status:	New	Start date:	
Priority:	Normal	Due date:	
Assignee:		% Done:	0%
Category:	Documentation	Estimated time:	0.00 hour
Target version:			
Resolution:		Affected version:	
Description			
I set up Redmine with nginx as a reverse proxy according to this HowTo: HowTo_configure_Nginx_to_run_Redmine			
For the most part it seems to work normally. Then I tried to delete a project which did not work. The HowTo's nginx configuration rewrites some "sensitive" paths to https and then rewrites back to http for "non-sensitive" paths except some paths that would be broken otherwise:			
<pre># Examples of URLs we don't want to rewrite (otherwise 404 errors occur): # /projects/PROJECTNAME/archive?status= # /projects/copy/PROJECTNAME # /projects/PROJECTNAME/destroy</pre>			
<pre># This should exclude those (tested here: http://www.regextester.com/ ) if (\$uri !~* "^/projects/.*(copy destroy archive)") {     rewrite ^/projects(.*) http://your.domain.here\$request_uri permanent; }</pre>			
As far as I can see these excluded paths are outdated. This does for example break the DELETE request upon project deletion.			
I worked around this by commenting out all the rewriting stuff and just defaulting to https with:			
server {     listen 80;			
return 301 https://\$server_name\$request_uri; }			
(In my opinion this is should be done anyways because data of non-public projects musn't be sent over http)			
The regex has to be updated to match the new path structure.			

#### History

#### #1 - 2016-02-06 05:09 - Toshi MARUYAMA

- Description updated

### #2 - 2016-02-06 05:13 - Toshi MARUYAMA

You can edit wiki.