

Redmine - Feature #23307

Get which auth_source_id of a user

2016-07-12 15:37 - Roger Mårtensson

Status: New	Start date:
Priority: Normal	Due date:
Assignee:	% Done: 0%
Category: REST API	Estimated time: 0.00 hour
Target version: Candidate for next major release	
Resolution:	
Description	
it would've been nice to be able to get which auth_source_id a given user has through the REST API. A nice complement to when creating user where it is possible to set the auth_source_id.	
Related issues:	
Related to Redmine - Feature # 23306: Support for authentication sources in R...	New
Related to Redmine - Feature # 36659: Add "auth_source_id" to GET request for...	New

History

#1 - 2016-08-09 17:38 - Toshi MARUYAMA

- Related to Feature #23306: Support for authentication sources in REST API added

#2 - 2018-02-06 18:01 - Anonymous

- File add_auth_source_id_to_api.patch added

I agree. This feature is also useful for admin scripts which needs to distinguish between "external" and LDAP users.

I attached a patch for this feature. auth_source_id only gets visible for admin users in it, as I do not see the need for standard users.

#3 - 2018-02-08 10:17 - Anonymous

@Toshi MARUYAMA : Do you have an opinion on this issue?

#4 - 2018-09-27 15:26 - Roger Mårtensson

What is the status of this issue?

#5 - 2018-09-27 15:35 - Go MAEDA

- Target version set to Candidate for next major release

#6 - 2019-09-07 02:47 - Go MAEDA

I think the response should include not only id but also name. Maybe the response does not include "auth_source" if the user uses internal authentication.

```
{
  "user": {
    "id": 1,
    "login": "admin",
```

```
"firstname": "Redmine",
"lastname": "Admin",
"created_on": "2006-07-19T17:12:21Z",
"last_login_on": "2019-09-06T06:37:53Z",
"auth_source": {
  "id": 1,
  "name": "LDAP test server"
}
}
```

#7 - 2019-09-08 05:03 - Go MAEDA

- File 0001-Add-auth_source-to-the-users-API-response.patch added

Here is a patch to add auth_source to the response of GET /users/:id.(xml|json). auth_source is included only when the users auth_source is not nil and the current user is an administrator.

```
"auth_source": {
  "id": 1,
  "name": "LDAP test server"
},
```

#8 - 2022-02-20 08:25 - Go MAEDA

- Related to Feature #36659: Add "auth_source_id" to GET request for Endpoint /users.:format added

Files

add_auth_source_id_to_api.patch	3.92 KB	2018-02-06	Anonymous
0001-Add-auth_source-to-the-users-API-response.patch	1.8 KB	2019-09-08	Go MAEDA