

Redmine - Patch #237

get journal from MailHandler.receive

2007-11-17 23:53 - Nobuhiro IMAI

Status:	Closed	Start date:	
Priority:	Normal	Due date:	
Assignee:		% Done:	0%
Category:		Estimated time:	0.00 hour
Target version:			
Description			
<p>Hello,</p> <p>here attached the patch to get Journal instance from MailHandler.receive.</p> <p>Adding notes via email can be done even now, but I want to get the instance of Journal that was added to the issue to send the notify mail by Mailer model.</p> <p>For example, the following solution will appropriately handle incoming mails with help from MDA and so on:</p> <p>Server side:</p> <pre>class MailHandlerController < ApplicationController session :off def import if local_request? begin journal = MailHandler.receive(File.read(params[:path])) Mailer.deliver_issue_edit(journal) if journal rescue => e logger.error("#{e.class}: #{e.message}") if logger end end render :nothing => true end end</pre> <p>Client side:</p> <pre>require "tempfile" require "open-uri" Tempfile.open("mail-to-import") do t t.write(ARGF.read) t.flush path = URI.escape(File.expand_path(t.path)) open("http://localhost/mail_handler/import?path=#{path}"){} end</pre> <p>I intend this for receiving mails without script/runner, that is too heavy to be invoked by each incoming mail.</p> <p>Thanks,</p>			

History

#1 - 2009-01-09 22:36 - Jean-Philippe Lang

- Status changed from New to Closed

Current trunk now behaves as expected here.

Files

journal-from-mail-handler.patch	475 Bytes	2008-02-03	Nobuhiro IMAI
---------------------------------	-----------	------------	---------------