

Redmine - Feature #2628

Set session store to cookie store by default

2009-01-30 17:59 - micah anderson

Status:	Closed	Start date:	2009-01-30
Priority:	Normal	Due date:	
Assignee:		% Done:	0%
Category:		Estimated time:	0.00 hour
Target version:	0.9.0		
Resolution:	Fixed		
Description			
It was said that in .7 that session store would be set to 'cookie store' by default over in this forum post: http://www.redmine.org/boards/2/topics/show/150			
However, the .8 version still has this set in environment.rb:			
<pre># Use the database for sessions instead of the file system # (create the session table with 'rake db:sessions:create') # config.action_controller.session_store = :active_record_store config.action_controller.session_store = :PStore</pre>			
I'm getting tens of thousands of sessions in my temporary directory daily. I clean them out with tmpreaper, but it seems better to stick them in the cookie store instead.			
perhaps there is a reason why this hasn't been set?			
Related issues:			
Has duplicate Redmine - Defect #3441: Too many session files		Closed	2009-06-03

History

#1 - 2009-01-30 18:51 - Jean-Philippe Lang

Setting cookie store by default is not so trivial since it requires a secret.
I never took the time to automate the process of generating a key at the first application start.

#2 - 2009-02-03 00:54 - Eric Davis

Mephisto has a rake task to automatically create a one. It's MIT licensed so we should be able to just use it:
http://github.com/emk/mephisto/blob/1473acf8307ec21d2002acab94691841d8003580/lib/tasks/session_store.rake

```
file 'config/initializers/session_store.rb' do
  path = File.join(RAILS_ROOT, 'config', 'initializers', 'session_store.rb')
  File.open(path, 'w') do |f|
    f.write <<"EOD"
# This file was generated by 'rake config/initializers/session_store.rb',
# and should not be made visible to public. Do not check it into github!
# If you have a load-balancing Mephisto cluster, you will need to use the
# same version of this file on each machine. And be sure to restart your
# server when you modify this file.

# Your secret key for verifying cookie session data integrity. If you
# change this key, all old sessions will become invalid! Make sure the
# secret is at least 30 characters and all random, no regular words or
# you'll be exposed to dictionary attacks.
ActionController::Base.session = {
  :session_key => '_mephisto_session_2',
  :secret      => '#{ActiveSupport::SecureRandom.hex(40)}'
}
EOD
end
end
```

#3 - 2009-02-20 10:19 - Javier Barroso

Hi,

Is it sure remove + 2 days old session files ?

```
1. df -i
/dev/sda4      294912 240644 54268 82% /opt
```

I have 179585 session files from 28 - 1 - 2009

Can I setup config/initializers/session_store.rb only adding it, is it necessary any step more ?

Thank you

Sorry for my english

#4 - 2009-02-20 23:09 - Eric Davis

Javier Barroso wrote:

Is it sure remove + 2 days old session files ?

Yes, I have a crontab to remove sessions that are older than 10 hours.

#5 - 2009-02-21 20:05 - Jean-Philippe Lang

- *Status changed from New to Closed*
- *Target version set to 0.9.0*
- *Resolution set to Fixed*

As of today, current trunk runs with Rails 2.2 and uses cookie store by default.
A rake task that generates a secret was added. Just run it once:

```
config/initializers/session_store.rb
```

#6 - 2009-03-05 16:32 - Javier Barroso

Thanks Eric (and Jean),

I was thinking it was problem from plugin, see my report at:

http://sourceforge.net/tracker/index.php?func=detail&aid=2636633&group_id=228995&atid=1075435

#7 - 2009-12-30 01:45 - Eric Davis

I just added a second rake task to generate the session_store.rb (it's an alias). There's been a lot of problems with rake config/initializers/session_store.rb, many people think that the session_store.rb file needs to exist before the command can be run.