

Redmine - Feature #26847

implement an upgrade script

2017-09-06 22:32 - fabrice salvaire

Status:	New	Start date:	
Priority:	Normal	Due date:	
Assignee:		% Done:	0%
Category:		Estimated time:	0.00 hour
Target version:			
Resolution:			
Description			
User can do mistake when they upgrade an existing instance, for example overwrite files in public from an older release.			
Some ideas			
<pre>#!/bin/bash redmine_version='3.4.2' archive_path='...' www_path='...' pushd \${www_path} tar xzf \${archive_path}/redmine-\${redmine_version}.tar.gz chown -R apache.apache redmine-\${redmine_version} pushd redmine-\${redmine_version} cp \${www_path}/redmine/config/database.yml config/ cp \${www_path}/redmine/config/configuration.yml config/ cp -r \${www_path}/redmine/plugins/* plugins/ # cp -r \${www_path}/redmine/public/... public/ cp -r \${www_path}/redmine/files/* files/ # patch -p0 < \${www_path}/redmine-patch.diff bundle install --without development test bundle exec rake generate_secret_token bundle exec rake db:migrate RAILS_ENV=production bundle exec rake tmp:cache:clear tmp:sessions:clear RAILS_ENV=production popd rm redmine ln -sf redmine-\${redmine_version} redmine apachectl restart</pre>			