

## Redmine - Feature #29588

### There should be a way to avoid adding paragraph to a Textile block

2018-09-11 23:59 - Senya Senya

<b>Status:</b> New	<b>Start date:</b>
<b>Priority:</b> Normal	<b>Due date:</b>
<b>Assignee:</b>	<b>% Done:</b> 0%
<b>Category:</b>	<b>Estimated time:</b> 0.00 hour
<b>Target version:</b>	
<b>Resolution:</b>	
<b>Description</b>	
<p>Currently I can see no appropriate way of avoiding adding <code>&lt;p&gt;</code> block to any Textile code. Any text enclosed with <code>\n</code> is currently being put to the <code>&lt;p/&gt;</code> tag.</p> <p>In php textile it is possible to avoid this by adding a space character in the beginning of the line (see <a href="https://txstyle.org/doc/2/paragraphs">https://txstyle.org/doc/2/paragraphs</a>):</p> <pre>  a line beginning with a space will be left untouched, and not wrapped in &lt;p&gt; ... &lt;/p&gt; tags</pre> <p>One of the cases where the issue is important is when using the <code>{{include}}</code> macro. Included pages are still enclosed in <code>&lt;p/&gt;</code> tag and this markup is usually wrong, because the included page is usually not a single paragraph, but contains some blocks, headers, etc itself.</p> <p>Currently there is a bug (#13695) in currently used Redcloth3, which makes a workaround for the described issue. When you start the line with some other tag, the remaining text will not be enclosed in a paragraph:</p> <pre>&lt;pre&gt;&lt;/pre&gt;@{{include(page)}}@</pre> <p>The same example can be used with the code tag instead of the pre tag which will also work this way.</p> <p>This can be used as a workaround, but since Redmine is slowly moving to RedCloth4 developers must ensure that the new Textile formatter will support not enclosing text blocks into paragraphs. In a quick scan of RedCloth4 doc I can't find a way to do so. Syntax like in php textile can be used for that, where "no-paragraph" is a line started with a space character.</p>	