

Redmine - Feature #3057

Allow custom my_page blocks to define drop-down names

2009-03-26 23:07 - Brad Beattie

| | | | |
|--|------------|------------------------|------------|
| Status: | Closed | Start date: | 2009-03-26 |
| Priority: | Normal | Due date: | |
| Assignee: | | % Done: | 0% |
| Category: | Plugin API | Estimated time: | 0.00 hour |
| Target version: | 0.9.0 | | |
| Resolution: | Fixed | | |
| Description | | | |
| <p>I have a plugin that adds additional blocks to the my_page page. The only problem I have here is that I can't name the blocks beyond their file names, whereas core blocks define their localized names:</p> <pre>BLOCKS = { 'issuesassignedtome' => :label_assigned_to_me_issues, 'issuesreportedbyme' => :label_reported_issues, 'issueswatched' => :label_watched_issues, 'news' => :label_news_latest, 'calendar' => :label_calendar, 'documents' => :label_document_plural, 'timelog' => :label_spent_time }.merge(Redmine::Views::MyPage::Block.additional_blocks).freeze</pre> <p>This request is necessary in order to localize the plugin.</p> | | | |

Associated revisions

Revision 2659 - 2009-04-05 15:33 - Jean-Philippe Lang

Set a default scope for 'My page' block names translations (#3057).

History

#1 - 2009-03-30 22:21 - Jean-Philippe Lang

Actually, you can add a key in your locales that matches the partial name, eg:

```
_my_partial.rhtml => uses 'my_partial' translation key if available
```

Maybe we could use a prefix for these translations in locales, eg: 'my.blocks.my_partial' or something.

What do you think?

#2 - 2009-03-30 22:33 - Brad Beattie

Jean-Philippe Lang wrote:

Actually, you can add a key in your locales that matches the partial name, eg:

```
_my_partial.rhtml => uses 'my_partial' translation key if available
```

Maybe we could use a prefix for these translations in locales, eg: 'my.blocks.my_partial' or something.

| What do you think?

Hrm. A prefix would be nice as it would help avoid any unintended overlap. Not necessary, but nice.

#3 - 2009-04-05 15:30 - Jean-Philippe Lang

- Status changed from *New* to *Resolved*

- Target version set to *0.9.0*

- Resolution set to *Fixed*

Committed in r2659.

Default scope is 'my.blocks', so you can have:

my:

blocks:

block_name: Localized block name

or (if not found):

block_name: Localized block name

#4 - 2009-11-15 14:23 - Jean-Philippe Lang

- Status changed from *Resolved* to *Closed*

#5 - 2011-10-25 13:00 - Jedidiah Lira

- Assignee deleted (*Eric Davis*)

SPAM