

Redmine - Defect #38868

Public URL or Logout Page showing back_url with Internal Server IP and Port

2023-07-20 07:56 - Caspion G

| | | | |
|--|--------|-------------------|-----------|
| Status: | Closed | Start date: | |
| Priority: | Normal | Due date: | |
| Assignee: | | % Done: | 0% |
| Category: | | Estimated time: | 0.00 hour |
| Target version: | | Affected version: | |
| Resolution: | | | |
| Description | | | |
| <p>I am using Redmine 5.0.1 with production environment on Windows 10 Professional.</p> <p>I installed it using Bitnami stack, and upgraded the ruby version to 3.1.4 and it ran successfully. Except I replaced Thin server with PUMA. Now when I use public URL/Domain name to access the site, it shows http://xxx_public_url/login?back_url=http%3A%2F%2F127.0.0.1%3A3001%2F</p> <p>I tried each and every step, but not finding any solution. I am using IIS for reverse proxy to internal puma server. Please help, as this is exposing my internal server for phishing attacks.</p> | | | |

History

#1 - 2023-07-20 08:01 - Caspion G

Caspion G wrote:

I am using Redmine 5.0.5 with production environment on Windows 10 Professional.

I installed it using Bitnami stack, and upgraded the ruby version to 3.1.4 and it ran successfully. Except I replaced Thin server with PUMA. Now when I use public URL/Domain name to access the site, it shows http://xxx_public_url/login?back_url=http%3A%2F%2F127.0.0.1%3A3001%2F

I tried each and every step, but not finding any solution. I am using IIS for reverse proxy to internal puma server. Please help, as this is exposing my internal server for phishing attacks.

My installation information is:

Environment:

| | |
|------------------|--|
| Redmine version | 5.0.5.stable |
| Ruby version | 3.1.4-p223 (2023-03-30) [x64-mingw-ucrt] |
| Rails version | 6.1.7.2 |
| Environment | production |
| Database adapter | Mysql2 |
| Mailer queue | ActiveJob::QueueAdapters::AsyncAdapter |
| Mailer delivery | smtp |

Redmine settings:

| | |
|---------------|--|
| Redmine theme | Purplemine2-master (includes JavaScript) |
|---------------|--|

SCM:

| | |
|-----|--------|
| Git | 2.38.0 |
|-----|--------|

Filesystem

Redmine plugins:

| | |
|-------------------|------------|
| additional_tags | 1.0.8 |
| additional | 3.0.9-main |
| redmine_kanban | 1.2.0 |
| redmine_resources | 1.0.8 |

#2 - 2023-08-31 18:34 - Holger Just

- Status changed from New to Closed

You have to configure your public hostname at **Administration -> Settings -> general -> Host name**. The value entered there is used to generate full URLs in some redirects and emails.