

Redmine - Feature #4282

Support for a) b) c) enumeration in wiki

2009-11-24 21:35 - Kamil .

| | | | |
|---|-----------------|-----------------|------------|
| Status: | New | Start date: | 2009-11-24 |
| Priority: | Low | Due date: | |
| Assignee: | | % Done: | 0% |
| Category: | Text formatting | Estimated time: | 0.00 hour |
| Target version: | | | |
| Resolution: | | | |
| Description | | | |
| Typing (for example) | | | |
| <pre>\$. foo \$. bar \$. something</pre> | | | |
| should result in | | | |
| <pre>a . foo b . bar c . something</pre> | | | |
| regards | | | |

History

#1 - 2009-11-26 19:12 - Jean-Philippe Lang

- Category set to Text formatting
- Priority changed from Normal to Low

#2 - 2013-04-09 14:36 - Dipan Mehta

+1. I really have the habit to follow a, b, c pattern over 1,2,3. This would be very useful addition.

#3 - 2013-04-09 14:41 - Dipan Mehta

Ideally, it would be even more interesting to have

```
# . foo
#$. foo-details
# . bar
#$. bar-details
#$. bar-details-2
# . something

1. foo
  1.a. foo-details
2. bar
  2.a. bar-details
  2.b. bar-details-2
3. something
```