Redmine - Defect #4920

Email notifications on file upload sent to empty recipient list

2010-02-24 15:43 - Jon Pascoe

| Status: | Closed | Start date: | 2010-02-24 |
|---|---|---|---|
| Priority: | Normal | Due date: | |
| • | | | 00/ |
| Assignee: | Jean-Philippe Lang | % Done: | 0% |
| Category: | Email notifications | Estimated time: | 0.00 hour |
| Target version: | 0.9.4 | | |
| Resolution: | Fixed | Affected version: | 0.9.2 |
| Description | | | |
| I have installed a var | nilla copy of Redmine 0.9.2.stable.3474 | 4 (MySQL) | |
| | | | |
| If I click "Send a test If I now go to a proje | email" from the bottom of the page, th ct with just myself as a member, and u erver logs for the receiving server, I car | pload a file, a delivery failure is | s bounced to the sending account. |
| If I click "Send a test If I now go to a proje Looking in the mailse qmail-queue-han qmail-queue-han | ct with just myself as a member, and u | pload a file, a delivery failure is n see that no receipients are so before-queue for qmail | s bounced to the sending account. et: |
| If I click "Send a test If I now go to a proje Looking in the mailse qmail-queue-han qmail-queue-han qmail-queue-han | ct with just myself as a member, and u erver logs for the receiving server, I can dlers[1697]: Handlers Filter dlers[1697]: from=redmine@*** | pload a file, a delivery failure is n see that no receipients are set before-queue for qmail **.co.uk c/local/psa/handlers/be | s bounced to the sending account. et: |
| If I click "Send a test If I now go to a proje Looking in the mailse qmail-queue-han qmail-queue-han qmail-queue-han qmail-queue-han | ct with just myself as a member, and u erver logs for the receiving server, I can dlers[1697]: Handlers Filter dlers[1697]: from=redmine@*** dlers[1697]: to= dlers[1697]: hook_dir = '/use | pload a file, a delivery failure is n see that no receipients are so before-queue for qmail **.co.uk c/local/psa/handlers/be | s bounced to the sending account. et: 1 started |
| If I now go to a proje Looking in the mailse qmail-queue-han qmail-queue-han qmail-queue-han qmail-queue-han qmail-queue-han | ct with just myself as a member, and u erver logs for the receiving server, I can dlers[1697]: Handlers Filter dlers[1697]: from=redmine@*** dlers[1697]: to= dlers[1697]: hook_dir = '/usp dlers[1697]: recipient[3] = | pload a file, a delivery failure is n see that no receipients are so before-queue for qmail **.co.uk r/local/psa/handlers/be | s bounced to the sending account. et: 1 started |
| If I click "Send a test If I now go to a proje Looking in the mailse qmail-queue-han qmail-queue-han qmail-queue-han qmail-queue-han qmail-queue-han | ct with just myself as a member, and u erver logs for the receiving server, I can dlers[1697]: Handlers Filter dlers[1697]: from=redmine@*** dlers[1697]: to= dlers[1697]: hook_dir = '/ust dlers[1697]: recipient[3] = h and without 'BCC' selected in the em | pload a file, a delivery failure is n see that no receipients are so before-queue for qmail **.co.uk r/local/psa/handlers/be | s bounced to the sending account. et: 1 started |

Associated revisions

Revision 3518 - 2010-02-28 18:18 - Jean-Philippe Lang

Adds a test for not sending email without recipient (#4920).

History

#1 - 2010-02-24 17:03 - Jon Pascoe

As per the FAQ, I modified my config/environments/production.rb settings so that mailer activities would be logged. As you can see, this confirms the issue of no recipient addresses being used:

```
Processing ProjectsController#add_file (for xxx.xxx.xxx at 2010-02-24 15:50:08) [POST]
Parameters: {"commit"=>"Add", "action"=>"add_file", "authenticity_token"=>"PhQkKzGZ2diEjdIdjsZHPootAQpWWElnx
4LkI22/I=", "id"=>"projectid", "controller"=>"projects", "attachments"=>{"1"=>{"file"=>#<File:/tmp/RackMultipa
rt20100224-84201-lashycm-0>, "description"=>"test"}}}
Sent mail to
Redirected to http://******.co.uk/projects/projectid/files
Completed in 508ms (DB: 3) | 302 Found [http://******.co.uk/projects/projectid/files/new]
```

#2 - 2010-02-25 23:49 - Jon Pascoe

Further to the details above ... My original installation of Redmine was on OSX. That copy is still installed, and still broken.

Since then I created a Fedora VM to test it out there, installed Redmine, and everything is working as expected.

Both installations are approximately identical, bar a few vendor packaging differences. Both use Apache, Passenger, MySQL, and rails versions. Also, they're both configured with the same email account/server for sending mail.

There is one difference ... Fedora has Ruby 1.8.6, and OSX has Ruby 1.8.7.

I find it hard to believe that is the problem though.

#3 - 2010-02-28 18:20 - Jean-Philippe Lang

Emails without recipients should not be sent. A test was added for that in <u>r3518</u> and it passes with ruby 1.8.7.

#4 - 2010-02-28 18:27 - Jon Pascoe

I have retested on OSX, with another user added to the project. Again, when a file is uploaded an email is generated with no recipients. The problem isn't that an email isn't being sent, but that an email is being sent without recipients.

Identical tests on my Fedora installation work perfectly, only my OSX installation is affected.

I have re-installed my OSX redmine from scratch, to be sure I haven't messed up the install, and the problem still occurs.

#5 - 2010-03-02 14:15 - Andrew Rudenko

I just want to add some details:

if submit any changes to the issues, we can see in production.log the message like this:

Sending email notification to: name1.surname1@email.domain.com, name2.surname2@email.domain.com, name3.surname 3@email.domain.com

but if we add a new document or upload a file, we can see another recipients list:

```
Sending email notification to: Namel Surnamel, Name2 Surname2, Name3 Surname3
```

and the notification is not received in the last case.

the logic for recipients has been updated in app/modules/mailer.rb for 9.2 version, and it seems not accurately well.

#6 - 2010-03-02 15:19 - Andrew Rudenko

I've changed app/models/mailer.rb a little and now all notifications are sent to their recipients

```
Index: app/models/mailer.rb
```

```
_____
 -- app/models/mailer.rb
                        (revision 3521)
+++ app/models/mailer.rb (working copy)
00 -114,11 +114,11 00
    when 'Project'
      added_to_url = url_for(:controller => 'projects', :action => 'list_files', :id => container)
      added_to = "#{l(:label_project)}: #{container}"
      recipients container.project.notified_users.select {|user| user.allowed_to?(:view_files, container.proj
ect)}
      recipients container.project.notified_users.select {|user| user.allowed_to?(:view_files, container.proj
ect) }.collect { |m| m.mail }
    when 'Version'
      added_to_url = url_for(:controller => 'projects', :action => 'list_files', :id => container.project_id)
      added_to = "#{l(:label_version)}: #{container.name}"
      recipients container.project.notified_users.select {|user| user.allowed_to?(:view_files, container.proj
ect) }
      recipients container.project.notified_users.select {|user| user.allowed_to?(:view_files, container.proj
+
ect) }.collect { |m| m.mail }
    when 'Document'
      added_to_url = url_for(:controller => 'documents', :action => 'show', :id => container.id)
      added_to = "#{l(:label_document)}: #{container.title}"
```

#7 - 2010-03-02 15:39 - Jon Pascoe

- Status changed from New to Resolved

- Assignee set to Jean-Philippe Lang

I've added those changes to my OSX installation and retested ... notifications for file uploads now work perfectly.

#8 - 2010-03-03 23:11 - Jean-Philippe Lang

- Status changed from Resolved to Closed
- Target version set to 0.9.4
- Resolution set to Fixed

#9 - 2010-03-03 23:20 - Jean-Philippe Lang

- Subject changed from Email notifications sent to empty recipient list to Email notifications on file upload sent to empty recipient list