

## Redmine - Defect #5012

### Redmine Fails to load stylesheets and Javascript when configured as suburi

2010-03-09 10:12 - Rajeev B

<b>Status:</b>	Closed	<b>Start date:</b>	2010-03-09
<b>Priority:</b>	Normal	<b>Due date:</b>	
<b>Assignee:</b>		<b>% Done:</b>	0%
<b>Category:</b>		<b>Estimated time:</b>	0.00 hour
<b>Target version:</b>		<b>Affected version:</b>	0.9.3
<b>Resolution:</b>	Invalid		
<b>Description</b>			
<p>I have installed redmine-0.9.3 on Windows7 and I started it with webrick as follows:</p> <pre>ruby script/server webrick -e production</pre> <p>It starts fine and I am able to access it with the url</p> <p><a href="http://localhost:3000/">http://localhost:3000/</a></p> <p>Now I want to configure redmine as a <b>suburi</b> and want to access it with url</p> <p><a href="http://localhost:3000/redmine">http://localhost:3000/redmine</a></p> <p>Following the instruction for suburi configuration I add the following line at the end of environment.rb</p> <pre>Redmine::Utils::relative_url_root = "/redmine"</pre> <p>When I restart webrick and access it with the suburi <a href="http://localhost:3000/redmine">http://localhost:3000/redmine</a> I get a lot of routing errors related to loading javascripts and stylesheets</p> <p>You can find the attached production.log file.</p> <p>Please help.</p> <p><b>More Configuration details:</b></p> <p>Windows7, Ruby 1.8.6, sqlite3, redmine-0.9.3</p> <p><b>Gems Installed:</b></p> <pre>cgi_multipart_eof_fix (2.5.0) fxri (0.3.6) fxruby (1.6.16) gem_plugin (0.2.3) hpricot (0.6.164) log4r (1.0.5) mongrel (1.1.5) mongrel_service (0.3.4) ptools (1.1.6) rack (1.0.1) rake (0.8.7) ruby-opengl (0.60.0) sqlite3-ruby (1.2.5) test-unit (2.0.1) win32-api (1.2.1, 1.2.0) win32-clipboard (0.4.4) win32-dir (0.3.2) win32-eventlog (0.5.0) win32-file (0.5.5) win32-file-stat (1.3.1) win32-process (0.5.9) win32-sapi (0.1.4) win32-service (0.5.2) win32-sound (0.4.1)</pre>			

## History

### #1 - 2010-03-09 13:09 - Rajeev B

- Status changed from New to Resolved

The Issue got resolved by starting redmine like this:

**`ruby script/server webric -e production -P /redmine`**

instead of what I did earlier like this:

**`ruby script/server webrick -e production`**

Now Whats left for me is to see it running over Apache 2.2

### #2 - 2010-07-13 00:28 - Holger Just

- Status changed from Resolved to Closed

- Priority changed from Urgent to Normal

- Resolution set to Invalid

### #3 - 2011-10-26 17:18 - jibiel jibiel

For those who bumping into this issue with **passenger** — just create symlink to public directory **inside directory itself**:

`ln -s /path/to/app/public/ /path/to/app/public/redmine`

## Files

production.log	8.56 KB	2010-03-09	Rajeev B
----------------	---------	------------	----------