

Redmine - Defect #5442

For help: How to let the TortoiseHg to incorporate Redmine user authentication and permissions, makes Mercurial server use Redmine permission system?

2010-05-05 09:47 - xiaoyu yin

Status:	Closed	Start date:	2010-05-05
Priority:	Urgent	Due date:	
Assignee:		% Done:	0%
Category:	SCM	Estimated time:	0.00 hour
Target version:		Affected version:	0.9.3
Resolution:	Invalid		
Description			
Environment:			
BitNami Redmine Stack			
(
- Redmine 0.9.3			
- Apache 2.2.14			
- ImageMagick 6.5.6-8-Q8			
- MySQL 5.0.83			
- Subversion 1.6.6			
- Ruby 1.8.7			
- Rails 2.3.5			
- RubyGems 1.3.5			
)			
TortoiseHg 1.0.1 (= Mercurial 1.5.1)			
Windows XP 2002 SP3			
expect: That is to say peoples can clone/commit/push/pull from my Mercurial server by http address(or https), and after type correct username and password of redmine.			
And another question is how does the http address map to the path of mercurial Repository on Mercurial server.			
Thank you!			

History

#1 - 2010-05-09 13:10 - Jean-Philippe Lang

- Status changed from New to Closed

- Resolution changed from Fixed to Invalid

Please, go to the forums or IRC to get help.