

Redmine - Defect #7002

mysql timeout when first browsing a large git repository

2010-11-30 02:16 - Chunlin Zhang

Status:	Closed	Start date:	2010-11-30
Priority:	Normal	Due date:	
Assignee:		% Done:	0%
Category:	SCM	Estimated time:	0.00 hour
Target version:		Affected version:	
Resolution:			
Description			
<p>This repository has 100000+ files,when firstly browsing it,the browser wait long time and show err: "" Internal error An error occurred on the page you were trying to access. If you continue to experience problems please contact your redMine administrator for assistance. Back ""</p> <p>And the redmine log err: ""</p> <p>Processing RepositoriesController#show (for 10.125.25.55 at 2010-11-29 13:49:16) [GET] Parameters: {"action"=>"show", "id"=>"android1", "controller"=>"repositories"}</p> <p>ActiveRecord::StatementInvalid (Mysql::Error: Lock wait timeout exceeded; try restarting transaction: INSERT INTO `changesets` (`committed_on`, `comments`, `commit_date`, `scmid`, `user_id`, `revision`, `repository_id`, `committer`) VALUES('2010-11-25 14:27:10', 'init', '2010-11-25 14:27:10', '6c8534b1713a29cfcc2fdaa7faee604a81fdbbce', 16, '6c8534b1713a29cfcc2fdaa7faee604a81fdbbce', 9, 'zhang <zhang@mymail.com>')): lib/redmine/scm/adapters/abstract_adapter.rb:298:in `save' lib/redmine/scm/adapters/abstract_adapter.rb:289:in `save' app/models/repository/git.rb:65:in `fetch_changesets' app/models/repository/git.rb:65:in `each' app/models/repository/git.rb:65:in `fetch_changesets' app/controllers/repositories_controller.rb:77:in `show'</p> <p>Rendering D:/webserver/Redmine/public/500.html (500 Internal Server Error) ""</p>			
Related issues:			
Related to Redmine - Defect #1931: Timeout risks: need asynchronous operations		New	2008-09-22
Related to Redmine - Defect #8143: Problem to update subtask		Closed	2011-04-13

History

#1 - 2010-12-03 06:26 - Chunlin Zhang

I have try several way to fix this.
At last,I found modify the git_adapter.rb @ 117 to
cmd = "#{GIT_BIN} --git-dir #{target("")} log --no-color --raw --date=iso --pretty=fuller --name-only "

Just add "--name-only",the repository page will get very fast!!

#2 - 2011-01-06 12:21 - Toshi MARUYAMA

- Category set to SCM

#3 - 2011-02-05 13:03 - Toshi MARUYAMA

- Status changed from New to Closed

Please see <http://www.redmine.org/projects/redmine/wiki/RedmineRepositories#Attaching-an-existing-repository-to-a-project> .

Important: When you first browse the repository, Redmine retrieves the description of all of the existing commits and stores them in the database.

This is done only once per repository but can take a very long time (or even time out) if your repository has hundreds of commits.

To avoid this, you can do it offline.

After having your repository declared in Redmine, run the following command:

```
$ ruby script/runner "Repository.fetch_changesets" -e production
```

All commits will be retrieved in to the Redmine database.