Redmine - Defect #7134

is_binary_data uses wrong heuristic to decide if a string is binary

2010-12-19 14:00 - Jérémy Lal

Status:	Closed	Start date:	2010-12-19	
Priority:	Low	Due date:		
Assignee:		% Done:	0%	
Category:	SCM	Estimated time:	0.00 hour	
Target version:				
Resolution:	Duplicate	Affected version:		
Description				
The is_binary_data method, used in repositories_controller.rb#124, is :				
<pre>def is_binary_data? (self.count("^ -~", "^\r\n") / self.size > 0.3 self.count("\x00") > 0) unless empty? end Applied to the attached file :</pre>				
<pre>str='' File.open("test_color.sh", "r") { f str = f.read } (str.count("^ -~", "^\r\n") +0.0)/ str.length => 0.311345646437995</pre>				
Which clearly is not < 0.3, so that file is downloaded instead of being displayed, when one want to view it.				
Related issues:				
Is duplicate of Redmine - D	Defect #6256: Redmine considers non ASCII and	UTF-1	Closed	2010-08-31

History

#1 - 2010-12-19 14:36 - Jérémy Lal

Ideally it should get the binary attribute from the SCM, but i don't know if all SCM have interface to get that information.

#2 - 2010-12-19 17:32 - Jean-Philippe Lang

- Category set to SCM
- Priority changed from Normal to Low

#3 - 2010-12-20 09:46 - ylgod jo

- Assignee set to Jim Mulholland
- % Done changed from 0 to 80

#4 - 2010-12-20 18:50 - Jean-Philippe Lang

- Assignee deleted (Jim Mulholland)
- % Done changed from 80 to 0

#5 - 2010-12-20 19:56 - Jean-Philippe Lang

- Status changed from New to Closed
- Resolution set to Duplicate

Same as <u>#6256</u>.

Files

test_color.sh

Jérémy Lal