Redmine - Feature #8195

Create an issue with custom fields values

2011-04-20 10:04 - Stéphane Schoorens

Status:	Closed		**Start date:**	2011-04-20
Priority:	Normal		**Due date:**	
Assignee:			**% Done:**	100%
Category:	REST API		**Estimated time:**	0.00 hour
Target version:				
Resolution:	Invalid			

Description

I need the custom field tag for a post action

related :
http://www.redmine.org/projects/redmine/wiki/Rest_Issues

History

#1 - 2011-04-20 10:53 - Etienne Massip

I think that it can be done ; did you try with

```xml
<?xml version="1.0"?>
<issue>
  <subject>Example</subject>
  <project_id>1</project_id>
  <priority_id>4</priority_id>
...
  <custom_values>
    <custom_value>
      <custom_field_id>2</custom_field_id>
      <value>Hello world !</value>
    </custom_value>
  </custom_values>
...
</issue>
```

?

#2 - 2011-04-20 10:54 - Etienne Massip

- Subject changed from REST API for posting an issue to Create an issue with custom fields values

#3 - 2011-04-20 11:11 - Stéphane Schoorens

I use my REST API for transform name into id
I use this type of data :
my $valeurs = {
issue => {
tracker => 'Anomalie',
status => 'In Progress',
priority => 'Urgent',
subject => 'new',
description => 'helloworld,
category => 'Module',
project => 'test',
custom_values => {
custom_value => {
custom_field_id => 3,
value[or name] => '123',
},
},
},
};
i'm using a json encoded and i post it after
and custom values doesn't work .

my api: https://github.com/sschoorens/Net--Redmine--API--REST
not yet on cpan i'm in dev

#4 - 2011-04-20 11:41 - Etienne Massip

custom_field_values is a safe attribute of Issue which requires the issue id as it's used for a many-to-many relationship and this case may not be handled by code in IssueController#build_from_params@ (source:trunk/app/controllers/issues_controller.rb#L311).

Maybe a subsequent /edit POST request to add the custom values with new issue's id specified could do the job, not sure though.

#5 - 2011-04-20 12:36 - Stéphane Schoorens

I've tried to make a PUT request on a issue with that values :

my $refhash = {
issue => {
custom_values => {
custom_value => {
custom_field_id => 12,
value => 'france',
},
},
notes => 'put custom',
},
};

but just the notes was added.

#6 - 2011-04-20 12:37 - Stéphane Schoorens

I've tried to make a PUT request on a issue with that values :

@my $refhash = {
@   issue => {
@   custom_values => {
@   custom_value => {
@   custom_field_id => 12,
@   value => 'france',
@   },
@   },
@   notes => 'put custom',
@   },
@@   };

but just the notes was added.

#7 - 2011-04-20 12:38 - Stéphane Schoorens

double post sorry can you remove it ? and how include code with @@?

#8 - 2011-04-20 14:01 - Etienne Massip

Surround your multiline code with

```
<pre><code class="javascript">...</code>
```


#9 - 2011-04-20 14:05 - Stéphane Schoorens

I've tried to make a PUT request on a issue with that values :

```
my $refhash = {
            issue => {
                    custom_values => {
                            custom_value => {
                                    custom_field_id => 12,
                                    value => 'france',
                                    },
                            },
                    notes => 'put custom',
                    },
            };
```

but just the notes was added.

#10 - 2011-04-20 17:16 - Etienne Massip

Could you try to edit issue with PUT /issues/[issue_id].json of

```
{
  issue => {
    custom_values => {
      custom_value => {
        customized_type => 'issue',
        customized_id => [issue_id],
        custom_field => 'my custom field',
        value => 'france',
      },
    },
    notes => 'put custom',
  },
};
```

?

#11 - 2011-04-21 09:14 - Stéphane Schoorens

I've tried this on a custom field who's name 'Origine' :

```
{
  issue => {
    custom_values => {
      custom_value => {
        customized_type => 'issue',
        customized_id => '424',
        custom_field => 'Origine',
        value => 'france',
      },
    },
    notes => 'put custom',
  },
};
```

Only the notes is put.

#12 - 2011-04-21 09:33 - Stéphane Schoorens

This is the return of json encode of an issue :

```
"custom_fields":[{"value":"","name":"Resolution","id":2}]
```

so I've tested the same like this :

```
{
        issue => {
            custom_fields =>[ {
                        id => '12',
                        value => '',
                        name => 'france',
            } ],
            notes => 'put custom',
        },
      };
```

but already only the notes are update.

#13 - 2011-05-25 20:54 - Etienne Massip

- Target version set to Candidate for next major release

#14 - 2011-05-26 00:32 - Etienne Massip

- Target version deleted (Candidate for next major release)

Could you please try the syntax described in [RE: REST API json/xml syntax for updating/creating issues](#) ?

#15 - 2011-05-26 14:59 - Stéphane Schoorens

- Status changed from New to Resolved

- % Done changed from 0 to 100

It works =p ! thanks you it works also with a POST

#16 - 2011-05-26 15:26 - Etienne Massip

If you have a few time, could you please add some doc about this in [REST issues wiki page](#), that would be very nice ?

Or simply copy a full working example here so I could update wiki page myself.

Thanks !

#17 - 2011-05-26 15:26 - Etienne Massip

- Status changed from Resolved to Closed

- Resolution set to Invalid

#18 - 2011-05-26 15:42 - Stéphane Schoorens

I've add the field for custom value in the wiki where the posting with json is explain

#19 - 2011-05-26 15:44 - Etienne Massip

Thanks a lot !

#20 - 2018-01-03 21:20 - Curtis Weatherford

Stéphane Schoorens wrote:

> I've add the field for custom value in the wiki where the posting with json is explain

Could you please add a link to this because I can't seem to find it.