

Redmine - Defect #8825

JRuby + Windows: SCMs do not work on Redmine 1.2

2011-07-15 13:27 - Toshi MARUYAMA

Status:	Closed	Start date:	2011-07-15
Priority:	Normal	Due date:	
Assignee:	Toshi MARUYAMA	% Done:	0%
Category:	SCM	Estimated time:	0.00 hour
Target version:	1.2.2	Affected version:	1.2.0
Resolution:	Fixed		

**Description**

SCMs on Redmine 1.1 work fine (some tests fail).  
SCMs on Redmine 1.2 on CRuby + Windows work fine, too.

But, SCMs on Redmine 1.2 on JRuby + Windows does not work due to 1.2 new feature [#7517](#).

```
R:\work\hg-workdir\redmine-all>jruby --version
jruby 1.6.2 (ruby-1.8.7-p330) (2011-05-23 e2ea975)
(Java HotSpot(TM) Client VM 1.6.0_23) [Windows Vista-x86-java]
```

**Mercurial, Git and CVS**

All tests fail with following error message.

In Japanese:  
ファイル名、ディレクトリ名、またはボリュームラベルの構文が正しくありません。

Translation to English:  
Filename, directory name, or volume label syntax is incorrect.

**Subversion and Darcs**

It seems that feature [#7517](#) does not work on JRuby + Windows.

**Bazaar**

Same with Subversion and Darcs on 1.2 stable.  
But trunk does not work.  
Because refactoring has started after [r5890](#).

**gem version on Redmine 1.1**

```
R:\work\hg-workdir\redmine-all>gem --version
1.5.1
```

You need to apply [jruby-gem-redmine-1.1.diff](#)

<b>Related issues:</b>		
Related to Redmine - Feature #7517: Configurable path of executable for scm a...	Closed	2011-02-02
Related to Redmine - Defect #9061: JRuby + Windows: CVS does not work	Closed	2011-08-16
Related to Redmine - Defect #9073: JRuby + Windows: Bazaar does not work	Closed	2011-08-17
Related to Redmine - Feature #12228: JRuby 1.7.2 support	Closed	

Associated revisions

**Revision 6272 - 2011-07-15 13:43 - Toshi MARUYAMA**  
scm: add new method "shell\_quote\_command" at abstract adapter (#8825).

**Revision 6273 - 2011-07-15 13:53 - Toshi MARUYAMA**

Merge(backport) r6230 from trunk (#8825).

scm: catch all exceptions at adapter shellout() to fork scm command.

If scm command does not exist,  
Linux JRuby 1.6.2 (ruby-1.8.7-p330) raises java.io.IOException in production environment.

#### **Revision 6274 - 2011-07-15 18:29 - Toshi MARUYAMA**

scm: subversion: use "shell\_quote\_command" method at adapter for JRuby + Windows command name (#8825).

#### **Revision 6275 - 2011-07-15 18:29 - Toshi MARUYAMA**

scm: darcs: use "shell\_quote\_command" method at adapter for JRuby + Windows command name (#8825).

#### **Revision 6276 - 2011-07-15 18:30 - Toshi MARUYAMA**

scm: cvs: use "shell\_quote\_command" method at adapter for JRuby + Windows command name (#8825).

#### **Revision 6277 - 2011-07-15 18:30 - Toshi MARUYAMA**

scm: cvs: use self.class.sq\_bin for command name at adpter scm\_cmd() (#8825).

#### **Revision 6278 - 2011-07-15 18:31 - Toshi MARUYAMA**

scm: mercurial: use "shell\_quote\_command" method at adapter for JRuby + Windows command name (#8825).

#### **Revision 6279 - 2011-07-15 18:31 - Toshi MARUYAMA**

scm: mercurial: use self.class.sq\_bin for command name at adpter scm\_cmd() (#8825).

#### **Revision 6280 - 2011-07-15 18:31 - Toshi MARUYAMA**

scm: git: use "shell\_quote\_command" method at adapter for JRuby + Windows command name (#8825).

#### **Revision 6281 - 2011-07-15 18:32 - Toshi MARUYAMA**

scm: git: use self.class.sq\_bin for command name at adpter scm\_cmd() (#8825).

#### **Revision 6282 - 2011-07-15 18:32 - Toshi MARUYAMA**

scm: bazaar: use "shell\_quote\_command" method at adapter for JRuby + Windows command name (#8825).

#### **Revision 6283 - 2011-07-15 18:33 - Toshi MARUYAMA**

scm: bazaar: use self.class.sq\_bin for command name at adpter scm\_cmd() (#8825).

#### **Revision 6284 - 2011-07-15 18:33 - Toshi MARUYAMA**

scm: bazaar: use self.class.sq\_bin for command name at adpter scm\_cmd\_no\_raise() (#8825).

#### **Revision 6447 - 2011-08-16 02:10 - Toshi MARUYAMA**

scm: add comment that configuration of SCM executable command does not work if contains spaces path to configuration.yml.example (#7517, #8825).

#### **Revision 6453 - 2011-08-17 13:14 - Toshi MARUYAMA**

Merge r6021 from trunk (#8825).

scm: fix JRuby tests fail in unit changeset following test.

- test\_invalid\_utf8\_sequences\_in\_paths\_should\_be\_replaced

Following Subversion functional tests fail on Japanese Windows + JRuby 1.6.2 (ruby-1.8.7-p330).

- test\_directory\_diff
- test\_revision\_diff

## **History**

---

### **#1 - 2011-08-16 08:14 - alvis lee**

+1

#2 - 2011-08-17 17:37 - Toshi MARUYAMA

- Status changed from New to Closed
- Target version set to 1.2.2
- Resolution set to Fixed

As I described at [r6447](#) comment and [source:trunk/config/configuration.yml.example@6447#L115](#), scm command path which contains spaces does not work.

CVS and Bazaar do not work.  
I created new issues.

- CVS [#9061](#)
- Bazaar [#9073](#)

Other scms pass tests.

Files

---

jruby-gem-redmine-1.1.diff	675 Bytes	2011-07-15	Toshi MARUYAMA
----------------------------	-----------	------------	----------------