

Redmine - Defect #9775

app/views/repository/_revision_graph.html.erb sets window.onload directly..

2011-12-11 21:34 - John Kubiawicz

Status:	Closed	Start date:	
Priority:	Normal	Due date:	
Assignee:		% Done:	0%
Category:	SCM	Estimated time:	0.00 hour
Target version:	1.3.1	Affected version:	1.3.0
Resolution:	Fixed		
Description			
<p>The subject says it all. The partial _revision_graph.html.erb (in app/views/repository) sets window.onload directly. As a result of setting window.onload directly, it toasts other onload events on the repository page (currently messing with a plugin that I have).</p> <p>Instead of:</p> <pre>window.onload = function() { stuff; };</pre> <p>should use the prototype syntax used elsewhere in Redmine:</p> <pre>Event.observe(window,"load",function(){ stuff; });</pre> <p>I believe that this started showing up when I pulled down the 1.2.2 updates (not entire sure of timeline)</p>			

Associated revisions

Revision 8209 - 2011-12-14 20:29 - Jean-Philippe Lang

Fixed that _revision_graph.html.erb breaks window load events (#9775).

Revision 8765 - 2012-02-04 12:06 - Jean-Philippe Lang

Merged r8209 from trunk (#9775).

History

#1 - 2011-12-14 20:29 - Jean-Philippe Lang

- Category set to SCM
- Status changed from New to Resolved
- Target version set to 1.3.1
- Affected version (unused) set to 1.3.0
- Affected version set to 1.3.0

Fixed in r8209.

#2 - 2012-02-04 12:06 - Jean-Philippe Lang

- Status changed from Resolved to Closed
- Resolution set to Fixed

Merged.